

11 | 12
14 | 13

FND. 2" ALUM. CAP
ME IN 1993 SURVEY
FOR COOPER CONSULTANTS

663.55' {663.50'}

BEARING BASE MY 1993 SURVEY FOR REID
N 89°25'14" W 1142.82' (1142.73')

EAST HIGHLAND AVE

NW COR. E 1/2,
NW 1/4, NW 1/4
SEC. 13

N 89°25'14" W 479.27' (479.23')

S 0°06'24" E
33.00'

150.02' [150.00']

150.01' [150.00']

179.24' (179.23')

S 0°06'05" E
33.00'

FND. 1/2" I. REBAR
ME IN 1993 SURVEY
FOR REID

SURVEYOR'S NARRATIVE:

THE PURPOSE OF THIS SURVEY IS TO STAKE THE LINE BETWEEN REID AND JOHNSON'S EAST LINE FOR POSSIBLE FENCE CONSTRUCTION.

I SURVEYED REID'S EAST LINE IN A 1993 SURVEY FOR REID AND THIS SURVEY AND THE BEARINGS ARE BASED ON THAT 1993 SURVEY. SHEA HAD SURVEYED JOHNSON'S WEST LINE IN A 1972 SURVEY FOR SAUNDERS AND I USED HIS MONUMENTS IN MY 1993 SURVEY FOR REID.

THIS SURVEY WAS CONDUCTED WITH A SOKKIA SET 300 TOTAL STATION AND A HUSKY DATA COLLECTOR.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

G. Dennis Edwards

OREGON
JULY 16, 1971
G. DENNIS EDWARDS
9 5 1
RENEWS 12/31/2009

(S 0°06'24" E) (WEST LINE, E 1/2, NW 1/4, SEC. 13)

JOHNSON
R. 144, P. 661

380.00'

REID
R. 55, P. 107


S 0°06'25" E 414.91' (S 0°06'24" E 415.00')

S 0°06'30" E 615.00' [615.00']

N 89°25'00" W 100.00'
50.00'
N 89°25'00" W
(N 89°25'00" W)

FND. 1/2" I. REBAR
ME IN 1993 SURVEY
FOR REID

194'
235.00'
200.10'
3.7'



LEGEND:

- FOUND MONUMENTS AS NOTED
- COMPUTED LOCATION FROM MY 1993 SURVEY FOR REID & MY 1988 SURVEY FOR PRIMM-DAULTON IN SEC. 12
- SET 5/8"X30" IRON REBAR WITH PLASTIC CAP #951
- {000} OF RECORD, MY 1993 SURVEY FOR REID
- {000} OF RECORD, MY 1988 SURVEY FOR PRIMM-DAULTON IN SEC. 12
- {000} OF RECORD, DEEDS

SURVEY FOR WALT REID
IN NW 1/4, NW 1/4 SEC. 13, T 4 N, R 28 E,
W.M., UMATILLA COUNTY, OREGON
06/08/2009 JOB# 50906046
EDWARDS SURVEYING P.O. BOX 763
541-567-3336 HERMISTON, OREGON 97838
DRAWN BY JMC

7-09
RK
07-106-B