



CURVE NO.	RADIUS	ARC	CHORD	CHORD BEARING
1	90.20	91.31	87.46	N 51°20'26"E
2	379.15	99.42	99.14	N 72°49'35"E
3	186.60	97.70	96.59	S 38°41'10"E
4	133.73	95.70	93.67	N 44°48'50"E
5	109.71	93.89	91.00	N 89°48'50"E
6	163.84	97.05	95.64	N 07°19'50"E
7	93.99	91.90	88.28	N 52°19'35"E
8	163.84	97.06	95.65	S 82°39'27"E

**Narrative:**  
 All center line monumentation is set based on found exterior boundary pins. The exterior boundary pins were used because most interior pins were found to not fit the bearings and distances by more than 0.1 feet.

**Note:**  
 Bearings based on plat.

**Legend:**  
 □ denotes set PK.  
 ● denotes found 3/8 pin, whose location were within 1/10  
 ○ denotes found 3/8 pin, locations incorrected.

REGISTERED  
 PROFESSIONAL  
 LAND SURVEYOR  
*Terry E. Harty*  
 GIBSON  
 JUL 14, 1978  
 TERRY E. HARTY  
 1638

**KRUMBEIN ENGINEERING CO**  
 ENGINEERS - SURVEYORS - PLANNERS  
 221 S. Main, Pendleton, Oregon

Survey for  
**C.P.R. CONSTRUCTION**  
 "McNary Township" Div. No. 5, Umatilla, Oregon

SCALE  
 1" = 100'  
 DATE  
 Dec. 14, 1978  
 DESIGNED BY  
 M.L.J.  
 CHECKED BY  
 D.H.K.  
 DRAWING NO.  
 75-204  
 Job No. 75-281