

to reach the usual road viewers oath: We called Ed D. Washburn and Edgar Thomson to chain and mark each of whom was qualified according to law, with a Mason Theodolite, I commence at 1/4 Sec 6 cor bet Secs 4 & 9 T 4 N R 33 E.

- Set initial post 20' west of corner, against fence on E. side of lane E. & W.
- North 2900 Center cor Sec 4
- 14725 Stone 1/4 Sec cor, marked the road angle on fence post and turn on true Sp line
- East 5158 Standard 1/4 Sec cor on S body Sec 33 in Sp 5 N 9 cut A on corner post of fences E. W. & N and turn along fence on reputed line N + S through center Sec 33
- North 5280 Set 1 m. P. 20' E of line
- 1775 Draw runs W.
- 1550 " " " deeper
- 2100 Summit
- 2300 Descend
- 1590 Cor fences N. S. & W purporting Center Sec 33
- 3150 Draw runs S. W.
- 4100 Summit
- 5280 Set 2 m. P. 20' E of line
- Continue on line N + S through center Sec 28
- 7611 Center of road in lane course E. & W.
- Set terminus 30' South and 20' East of Pt on line by wire fence on South side of lane.

I hereby certify that the foregoing is a correct copy of the original field notes of Road No 339 for Multnomah County Oregon.

Jno. G. Arnold
Co Surveyor.

Filed July 9th 1890 }
Wm Pierce Clerk
C.S.

The
of Road
Meridian

Filed in
Wm P.