

- 4741 ft Ret 13 and turn thence R. 83°, 05'.
 N 13°, 12' W 5250 .. " 2 m post, which is a regulation post. fir. 30' W of line in E. Mound
 4 ft base x 2 ft high, continue last course.
 128 .. Ret 14, angle in lane S 92° W, turn thence S 81°, 40'
 S. 85°, 08' W along lane on reputed line bet pccs 27th & 34.
 400 .. Ascend hill.
 515 .. Summit. Descend.
 700 .. Dry Gulch. Course N. E. - ascend.
 1300 .. Summit - Level.
 1400 .. Descend.
 1800 .. Dry Gulch - Ascend.
 2350 .. Summit - Descend. 25'.
 S 85°, 08' W 2616 .. Wire fence, N 92° S. through center - pcc 34.
 Ret 15 and turn thence S. 83°, 05' along lane N 92° S.
 S 2°, 03' W 3200 .. Ascend hill.
 3900 .. Summit.
 4050 .. Descend and at 4200' Dry gulch, Course N. E. - ascend.
 5030 .. S. end of lane, set terminal post on line, a fir 4" x 4" x 4", in md. of E.
 4 base x 2 high, post mtd R 441, on N face.

I hereby certify that the foregoing are the correct field notes for
 Road Survey No. 441, for Umatilla County, Oregon.

Jno. C. Arnold, Co. Surveyor.

Filed June 30, 1894.

W. M. Pierce, Clerk.

By C. M. Peice, Deputy.