

				L	R	
Hence	S 82° 30' E	775	6775	29°		151
"	S 81° 30' E	408	7183	1°		152
"	N 83° 15' E	415	7598	15° 15'		153
"	S 85° E	402	8000	8° 30'		154

9 Nails, A pine 20 inches diameter 20'

Left, Marked 9 M.

Hence S 51° 15' E 524 524 R.T. Marked Stone from which the SE corner of Sec 19

J 2 S R 34 E N 11

Bears N 75° 15' E 11.36 chains distance

a fir 15 inches dia N 26° E 41 lbs

a pine 6 " " N 88° W 20 lbs

I hereby certify that the foregoing is a true transcript of the field notes of Road N° 500, as surveyed by me, commencing on the 27th day of Oct. 1898

John W Kimbrell

Surveyor for Umatilla County, Oregon

Filed November 3^d 1898

B. S. Durruths, Clerk (List recorded in P. D. Plat Book N° 1 Pages 53^d & 67)

ROAD N° 502

In the Matter of Viewing, Surveying and Laying Out County Road N° 502

To The Honorable County Court of the State of Oregon for Umatilla County:

We the undersigned, the Viewers heretofore appointed to view and locate Road N° 502, submit the following report: Pursuant to an order of the Honorable Court we met John W Kimbrell, Surveyor, at B N French's house on the 25th day of November, 1898, and were by him, each, duly sworn to faithfully and impartially discharge the duties of our appointments.

We called to our aid Elias Reeves, G J Calder, Chairman, N B Banks, marker, who were by the surveyor, each, duly sworn. We viewed surveyed and located said road N° 502, as specified in our order and find the route practicable and recommend the same be established as a public highway, as per petition.

E Eads	} Viewers Road Survey N° 502
J E Clark	
W M Banks	

Field Notes of Road Survey N° 502

I commenced at the S.E. corner, Sec 27 T 5 S R 32 E N 11; Set post 4x4x48 inches in mound of stone 18 inches high, 48 inches wide at Base in corner point Marked "R. 502";

		Chains	Distance	L	R
Hence	West	58.25			
"	N 58° W	1.60	59.85		58°
"	N 35° W	2.50	62.35		23°

dia. 20
8 M