

ROAD NO  
519

of range 32 East from which point north 20 feet 1 set post  
3 1/2 feet long marked R 519. 15 inches in the ground raised  
mound and dug pits. thence East on center line of section  
24.

58+65 intersect Reservation line at 1/4 corner on east line of  
said section 24 from which north 20 feet 1 set post 3 1/2 ft  
long marked R 519. 15 inches in the ground dug pits and  
raised mound as per requirements C.E. Macomber County  
Surveyor

This is to certify that the notes herein contained are  
the correct field notes of Road # 519 as surveyed by me Oct  
19th A.D. 1900 C.E. Macomber Surveyor

for Umatilla County Oregon  
Filed Nov 1st 1900

W.D. Chamberlain Clerk

ROAD NO  
520

In matter of viewing laying out and surveying County  
Road No 520. To the Honorable County Court of the State of Oregon  
for Umatilla County, we the undersigned the viewers heretofore  
appointed to view and locate Road No 520. Submit the following  
report pursuant to an order of the Honorable County  
Court we met C.E. Macomber Surveyor at the residence of  
J.W. French on the 22nd day of October A.D. 1900. and were  
by him each duly sworn to faithfully and impartially  
discharge the duties of our appointments we called to our  
aid Wm Cooper and C.E. Macomber Chommen, and  
Wm Cooper Marker, and were each duly sworn. We  
viewed located and surveyed said road # 520, as specified  
in our order, and find the route practicable and we most  
respectfully recommend that said road be constructed  
and established and declared a public highway of  
Umatilla County Oregon

John W. French  
Donald Rasmussen  
A A Cole

Field notes of Road # 520, beginning at a Stone Monument on  
west side of Old road, near the center of the NW 1/4 of section 9  
T 2 South R 30 East W.M said stone being at a point where  
the easterly and westerly line fence between the lands of  
James Nelson and J.P. Boherty intersect said old road  
20 feet south from said Stone. 1 set post 3 1/2 feet long  
marked R 520 15 inches in the ground dug pits and raised  
mound thence along said line fence

dug pits C.T. 20  
37°  
3°30'  
north of the S.E.  
corner 20x10x5  
mound of  
city Surveyor  
old notes of  
Surveyor  
of Oregon  
surveying  
of Oregon  
appointed  
report  
C.E. Macomber  
the 19th day  
m. to faith-  
re appoint-  
er E.N. Smith  
sworn heard  
in our  
most  
constructed  
highway of  
the north  
ownership one