



NARRATIVE:

THE PURPOSE OF THIS SURVEY WAS TO SET THE S.W. CORNER OF MY CLIENT'S PROPERTY, ON THE EAST R/W LINE OF THE RAILROAD. I ALSO SET A R.R. SPIKE AT THE S.E. 1/4 COR. SEC. 35, AS THIS CORNER CONTROLS THE PROPERTY CORNER..
 I SET THE SE 1/4 COR. SEC. 35 AT THE INTERSECTION OF THE N-S AND E-W CENTERLINES OF THE SE 1/4 SEC. 35 AS CONTROLLED BY FOUND 1/4 CORNERS AS SHOWN.
 ALL CORNERS WERE TIED BY CLOSED TRAVERSE, USING THEODOLITE AND E.D.M.

LEGEND

- MONUMENT FOUND AS NOTED
- ⊙ MONUMENT FOUND AS NOTED
- MONUMENT SET AS NOTED

RECEIVED BY
 Umatilla County Surveyor
 Date April 1985
 Rec'd By KA
 No. 85-61-A

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

Victor M. McLind

OREGON
 JULY 17, 1970
 VICTOR M. MCLIND
 934

SURVEY IN SE 1/4 S. 35, T6N, R35E
 SURVEYED FOR VERNON RODIGHIERO
 SURVEYED BY VICTOR MCLIND, LS. 934
 APRIL, 1985 SCALE: 1" = 200'
 BEARING BASE: THE N-S CENTERLINE OF SE 1/4 SEC. 35 AS PER C-S FILE # S-112