

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


R-13
400300

T. 1 N., R. 36 E.
Corner of sections 21, 22, 27 & 28

History of original corner establishment:

1882, Herman D. Graddon, U.S. Deputy Surveyor, while subdividing the township under GLO Contract No. 452 established the corner as follows:

Set a basalt stone 20 X 12 X 8 ins, 15 ins in the ground, for Cor to Sec's 21, 22, 27 + 28, marked with 2 notches on S. and 3 notches on E. edges from which
A fir 18 ins diam, bears N. 45° E. 37 lks dist, marked T1N.R36E.S22.B.T.
A fir 28 ins diam, bears S. 85° E. 72 lks dist, marked T1N.R36E.S27.B.T.
No other trees within limits and raised a mound of stones alongside



1997-99, Kaiser, Griffin and Seibold, BLM Cadastral Surveyors, reestablish the corner as follows:

Point for the cor. of secs. 21, 22, 27, and 28, at proportionate distance; there is no remaining evidence of the original cor.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap from which
A ponderosa pine, 8 ins. diam. bears N. 21° E., 43 lks. dist., mkd. T1N R36E S22 BT.
A ponderosa pine, 11 ins. diam. bears S. 78° E., 53 1/2 lks. dist., mkd. T1N R36E S27 BT.
A ponderosa pine, 11 ins. diam. bears S. 2° W., 96 1/2 lks. dist., mkd. T1N R36E S28 BT.
A ponderosa pine, 10 ins. diam. bears N. 74 1/2° W., 30 lks. dist., mkd. T1N R36E S21 BT.
Deposit a magnet in a white plastic case at the base of the stainless steel post.

2000, David L. Haddock, Registered Land Surveyor 852, while surveying in sections 21 and 22 for the Umatilla N.F., finds evidence of the original 1/4 corner of sections 21 & 22 and the original 1/4 corner of sections 22 & 27. This makes the BLM monument an erroneously established corner.

2001, Richard S. Kaiser, BLM Cadastral Surveyor, corrects the BLM's corner as follows:
Point for the cor. of secs. 21, 22, 27, and 28, at proportionate distance; there is no remaining evidence of the original cor.. From this point, the cor. of secs. 21, 22, 27, and 28, erroneously reestablished by Kaiser, Griffin, and Seibold in 1997-99, bears N. 0°38'02" E., 55.98 ft. dist.; monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. and witnessed as described in the official record. I obliterate all marks on the SE. and the NW. bearing trees.

Remove the stainless steel post and magnet and at the true corner point
Reset the stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap
from which the bearing trees mkd. by Kaiser, Griffin, and Seibold
A ponderosa pine, 8 ins. diam., bears N. 7 1/2° E., 83.1 ft. dist., with scribe marks
T1N R36E S22 BT visible on partially healed blaze.
A ponderosa pine, 11 ins. diam., bears S. 11 1/2° W., 8.0 ft. dist., with scribe marks
T1N R36E S28 BT visible on partially healed blaze.
and new bearing trees
A ponderosa pine, 14 ins. diam., bears S. 72 1/2° E., 68.4 ft. dist., mkd. T1N R36E S27 BT
A ponderosa pine, 6 ins. diam., bears N. 57 3/4° W., 32.1 ft. dist., mkd. X at breast height and BT at the base.
Deposit a magnet in a white plastic case at the base of the stainless steel post.
Corner is located in an abandoned roadbed, 5 ft. N. of a 4 strand barbed wire fence, bears NW. and SE.

Description of corner evidence found:

Found a 2 1/2" diameter stainless steel pipe, with 3 1/4" diameter brass cap, projecting 7" out of the ground, surrounded by a ring of stones, located on the West edge of a dirt road, marked as shown, from which:
8" Ponderosa Pine bears N 7 1/2° E, 83.1 feet, with scribing visible on pitched over blaze.
14" Ponderosa Pine bears S 72 1/2° E, 68.4 feet, with scribing visible on pitched over blaze.
11" Ponderosa Pine bears S 12 1/4° W, 8.0 feet, with scribing visible on pitched over blaze.
6" Ponderosa Pine bears N 57° W, 32.1 feet, with scribing visible on partially healed blaze.

Description of monument and accessories I established to perpetuate the original location of this corner:

DATUM: NAD83(1991) Oregon High Accuracy Reference Network
STATE PLANE COORDINATES: Oregon North Zone in International Feet
No. Latitude Longitude Northing(Y) Easting(X)
400300 45°32'38.21242" N. 118°18'28.75140" W. 692028.819' 8763631.285'

Work Performed By: David A. Schlaich (RLS 2308)
Witnessed By: Matthew Duffy
Equipment: Topcon GPT-6005C Total Station
Magnetic Declination: 17 1/2° East
Date: July 25, 2002



REGISTERED
PROFESSIONAL
LAND SURVEYOR

David A. Schlaich

OREGON
JULY 16, 1987
DAVID A. SCHLAICH
2308

RENEWAL DATE: 06/30/2004

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 20.....

..... by.....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

SEE MAP OF SURVEY NO. 03-31-B