


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

C-E 1/6 Cor. Sec. 1, T3N R37E

History of original corner establishment:

No Record



C-24

Description of corner evidence found:

NONE

Description of monument and accessories established to perpetuate the original location of this corner:

SET A 2" x 30" ALUMINUM PIPE WITH 2 1/2" ALUMINUM CAP, MARKED AS SHOWN ABOVE, 24" IN GROUND, FROM WHICH:

- A FIR, 14" DIAM., SCRIBED "CE 1/6 S 1 BT" BEARS N 46 1/4° E, 70.2 FT.
- A FIR, 13" DIAM., SCRIBED "CE 1/6 S 1 BT" BEARS N 82 1/2° W, 40.0 FT.

SET A STEEL POST 3' SOUTH OF CORNER, WITH SIGN 54-4.
 PAINTED A RED BAND AROUND BOTH BT'S, AND ATTACHED SIGNS 54-3 ABOVE BLAZE, AND SIGNS 54-4 TO BACK OF TREES.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Victor M. McLind
 OREGON
 JULY 17, 1970
 VICTOR M. MCLIND
 934

RECEIVED BY
 Umatilla County Surveyor
 Date 7-31-86
 Rec'd By KA
 No. 86-97-R

Office of SURVEYOR County of UMATILLA
 State of OREGON, I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)