


History of original corner establishment:
None




x-16

Description of corner evidence found:
None

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x 30" Iron pipe with brass cap 25" in ground stamped in a mound of stone, from which:
A 11" fir bears S 81 1/2° W 12.8 ft scribed CE 1/16 S 34 BT
a 11" fir bears S 35° E 11.5 ft scribed CE 1/16 S 34 BT



I nailed alum. tags stamped 951 to bottom of blazes and painted blazes red. Painted red band around BT's and nailed USFS signs 54-3 and 54-9 to them.

Drove a steel fence post 3 ft north and attached 54-9 sign.

I hereby certify the above corner location was perpetuated as herein described in July 1985.

Jud Coppock Jud Coppock, Witness

REGISTERED
PROFESSIONAL
LAND SURVEYOR

G. Dennis Edwards

OREGON
JULY 18, 1971
G. DENNIS EDWARDS
951

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....
..... by

(COUNTY OFFICIAL)

(DEPUTY)

Form R6-7100-57 (9/71)

RECEIVED BY
Umatilla County Surveyor
Date 8-6-85
Rec'd By KA
No. 85-108-R
95-C