

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


2-3

History of original corner establishment:

Corner established by George S. Pershin under GLO contract No. 304 dated Sept. 19, 1978


- A Pine Post
- A Fir 8" dia. N 70°E 8 lks
- A Fir 18" dia, S 5°W 36 lks
- 1½" Galvanized pipe with a 2½" Brass Cap

Set in 1976 by James Hanley under a U.S. Forest Service Contract



Description of corner evidence found:

Found a 1½" Galvanized pipe with a 2½" Brass Cap set 20" in ground
A 14" White Fir bears N 73°W 33.0 feet mkd T4N R38E S 31 BT



Description of monument and accessories established to perpetuate the original location of this corner

Scribed:

A 7" Spruce N 87°E 60.0 feet mkd T4N R38E S 31 BT

Blaze is painted red, tree has a red band painted around it and has sign numbers 54-3, 54-4, and has a Brass Washer stamped PLS 933 nailed to it.

November 1982

By: D. Krumbein
Witness: R.D. Panches



Office of Surveyor County of Umatilla
Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 22 day of July 1983
David H. Krumbein by _____
 (COUNTY OFFICIAL) (DEPUTY)

RECEIVED BY
 Umatilla County Surveyor
 Date 9-13-83
 Rec'd By BC GPO 796-22
 No. 83-171-R