


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established.



S-25

Description of corner evidence found:

N/A

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 3"x30" galv. iron pipe with 3" brass cap stamped as shown on the diagram. Set pipe 16 inches in the ground and raised a mound of stone around the pipe.

From which:

A pine 16 inches dia. bears N39°E, 7.7 ft. scribed N 1/16 S 30 BT.

A pine 16 inches dia. bears S64°W, 8.5 ft. scribed N 1/16 S 25 BT.

Set steel posts with warning and boundary signs 6 ft. West and 5 ft. South from corner.

Nailed brass washers stamped PLS 848 and bearing tree signs to each tree. Painted red band around each tree.

I hereby certify that the above corner monument was established on 7/28/81 as herein described.

Witness: D. Mitchell Ferguson

REGISTERED
PROFESSIONAL
LAND SURVEYOR

[Signature]
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Mike Woodward

Office of.....Co. Surveyor..... County of...Umatilla.....
State of.....OREGON....., I hereby certify that the within instrument was filed in this office
for record on the...28... day of...January... 1981
.....David...Krum... by *Billy...Halt*.....
(COUNTY OFFICIAL) (DEPUTY)