

Index

File No. A-11

CORNER RECORD (SEARCH)

(Ref. FSM 7151.4)

Tract or

Survey No. _____

Cor.

No. _____

T 5N R. 38E

R.D. WALLA WALLA

County

UMATILLA

Merid. WILLAMETTE

N.F. UMATILLA

State

OREGON

CORNER DIAGRAM



T6NR38E

1/4 54

T5N

1980

PLS 1294

DESCRIBE CORNER MONUMENT FOUND

BRASS CAPPED IRON PIPE SET BY PERRY IN 1980
FROM ORIGINAL EVIDENCE - FOUND BY BLM
& ACCEPTED.

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

PHOTO IDENTIFICATION DATA

Photo No. _____

Filed At. _____

Object Ident. _____

Ident. By _____

Signature

PLANE COORDINATE POSITION DATA

State _____ Zone _____

X _____

Y _____

Estab. By _____

Agency

Signature

Title

Division

Headquarters

Date

1990

FS-7100-52 (3/68)

4

5

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

Work Done By _____ Title _____ Date _____ State Registration No. _____
or Agency _____
Certified Cor. Record Prepared? Yes No Filed At: _____ Date _____

REMARKS

Index File No.

T.

R.

M.

Tract or Surv. No.

Cor.

12

13

USDA-FOREST SERVICE

Index
File No. A-11

CORNER RECORD (SEARCH)


(Ref. FSM 7151.4)

Tract or
Survey No. _____ Cor.
No. _____

T 5N R. 38E R.D. W² County UMATILLA

Merid. WILL N.F. UMATILLA State OREGON

CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

PHOTO IDENTIFICATION DATA

Photo No. _____

Description of corner evidence found: I could find no trace of original stone set in 1872 or 1899. Found dead Fir snag 27" diam with visible scribing "1/4 S BT". At record bearing & dist found 3/4" steel pin next to old blaze line tree with blazes on 4 sides.

Signature _____

PLANE COORDINATE POSITION DATA

State _____ Zone _____

X _____

Y _____

Estab. By _____

Agency _____

Signature

(S) HOWARD L. PERRY

Title

PLS

Division

1294

Headquarters

Date

9/80

7100-52-(3 68)

CORNER RECORD (PERPETUATION)

Description of monument and accessories established to perpetuate the original location of this corner: In place of 3/4" pin set 1"x30" pipe with brasscap 3" diam stamped:

Set pipe 20" in ground with mound of stone to cap.
Bearing trees:

Old: A dead White Fir snag 27" dia bears S70°E, 15.2 ft with visible "1/4 S BT".

New: A White Fir 14" dia bears S70°W, 17.3 ft scribed 1/4 S4 BT.
A White Fir 12" dia bears S72°E, 27.0 ft scribed 1/4 S4 BT.

CROWN ZELLERBACH
T6N R38E

1/4 ———
S4
T5N
1980
OR PLS 1294

Attached 54-3 & 54-4 signs to all BT's.

Attached brass washer stamped LS 1294 to foot blaze of new BT's. Painted blazes & 6" band around all BT's.

Work Done By _____ Title _____ Date _____ State Registration No. _____
or Agency _____

Certified Cor. Record Prepared? Yes No Filed At: _____ Date _____

REMARKS

Index File No.	T.	R.	M.	Tract or Surv. No.	Cor.
A-11	5N	38E			

T6N

A-11

$\frac{1}{4}$ $\frac{33}{4}$

R38E

TSN

ORIGINAL SURVEY IN 1872 BY WILLIAMS

RESURVEY AND NEW CORNER SET IN 1899 BY CAMPBELL

SEARCH AREA IS LOCATED ON A STEEP SE SLOPE IN MODERATELY THICK STAND OF VIRGIN TIMBER.

LOCATION WAS DETERMINED BY MEASUREMENT FROM VICINITY OF $\frac{32}{5}$ $\frac{33}{4}$.

ORIG. SURVEY CORNER WAS A STONE AND NO BT'S, RESURVEY CORNER IS ALSO A STONE AND ONE FIR BT. THERE ARE MANY STONES IN THE SEARCH AREA. WE ARE UNABLE TO FIND ANY EVIDENCE

OF SURVEY LINES (BLAZES, AXE MARKS, ETC.) IN THE AREA. NEITHER SURVEY NOTES THE BEGINNING OF THE DESCENT, WHICH IS VERY ABRUPT, TO THIS CORNER. OUR SEARCH LOCATION IS IN REASONABLE HARMONY WITH THE SURVEY LINE LOCATION PER USGS TOPOG. MAP.

NO EVIDENCE FOUND.

5-29-70

Greg J. Janitz ORS 1099
GREG ORTON

COMPASS DECL. 19 1/2° EAST.

A-11

USDA-FOREST SERVICE

PH
FIL

T

MAY 30 1970

1 2

PH
FIL
OR
LBS

FL
ST
X
Y
ELEV