

Subdivisional lines, T. 1 N., R. 35 E.

Chains	(For explanation, see page 67, Corrections of Subdivisions). A pine 14 ins. in diam. bears S.9° E. 73 lks. dist., marked $\frac{1}{4}$ S. B. T. A pine 24 ins. in diam. bears N. 54 $\frac{1}{2}$ ° W. 93 lks. dist., marked $\frac{1}{4}$ S.B.T.
50.00	Summit of rocky spur , course W. Across head of ravine.
60.00	Summit of rocky spur, course N.W. Descend 75 ft.
65.00	Bottom of ravine - opens W. Ascend 100 ft.
75.30	Summit of rocky point - descend.
77.50	Ravine, 50 ft. deep - creek 2 lks wide, course S.W.
80.00	Set a fir post 3 ft. long, 4 ins. square, 24 ins. in the ground for cor. to secs. 25, 26, 35 and 36; marked T.1 N.S. 25 on N.E.; R.35E.S36 on S.E.; S.35 on S.W., and S.26 on N.W. faces, with 1 notch on S. and E. edges, from which A black pine 16 ins. in diam. bears N.70° E.58 lks. dist., marked T.1 N.R.35 E. S.25 B.T. A black pine 15 ins. in diam. bears S.36° E.26 lks. dist., marked T.1 N.R.35 E. S.36 B.T. A black pine 6 ins. in diam. bears S.50 $\frac{1}{2}$ ° W. 58 lks. dist., marked T.1 N.R. 35 E. S.35 B.T., and A black pine 20 ins. in diam. bears N.71-3/4° W.27 lks. dist., marked T.1 N.R.35 E. S.26 B.T. Land, hilly- mountain top. Timber-heavily timbered with pine, fir, spruce and tamarac - 80 chs. Mountainous lands - 80.00 chs. Soil, loam- 2nd rate.
	East on random line bet. secs. 25 and 36. Var. 18°35' E.
40.00	Set temporary $\frac{1}{4}$ Sec. cor.
80.30	Intersect E. bdy. of Tp. 21 lks. S. of cor. to secs. 25, 36, 30 and 31, which is a post 2 ft. above ground, marked and witnessed as described by the Surveyor General: Thence, I run S.89° 51' W. on true line bet. secs. 25 & 36 along O.R.&N.