Subdivisional Lines, T.11S., R.35 E.,W.M.

Chains		Feet
	A fir, 6 ins. diam., brs. N.53°W., 22 lks. dist., marked T.1 S., R.35 E., S.22,B.T.	
	A fir, 10 ins. diam.,brs. S.62°W.,35 lks. dist., marked T.1 S.,R.35 E.,S.27,B.T.	
	A fir, 12 ins. diam., brs. S.41°E.,14 lks. dist., marked T.1 S., R.35 E., S.26,B.T.	
	Land;high and mountainous.	
	Soil; 2nd & 3rd rate.	
	Heavily timbered with fir, tamarack, pine and spruce, 72.19 chs.	
	Dense undergrowth of fir, tamarack, pine and spruce.	
	E. on random bet. Secs. 23 & 26. Var. 19°30' E.	
7.50	Top of hill, brs. N.W. & S.E., 150 ft. above Sec. Cor.	
8.00	Descend hill, brs. N.W. & S.E.	
16.80	Dry bed of creek, 3 lks. wide, course N.W., 200 ft. below top of hill. and ascend.	
28.00	Enter opening, brs. N.W. & S.E.	
36.00	Leave opening and enter timber, brs. N.W. & S.E.	
39.50	Top of hill, brs. N.W. & S.E., 400 ft. above bed of creek.	
40.00	Set temp. ¼ Sec. Cor.	
41.00	Descend hill, brs. N.W. & S.E.	
52.00	Dry gulch, course N., 150 ft. below top of hill.	
77.60	Foster's toll road brs. N.15°E. and S.15°W.	
80.00	Intersect N.& S. line at Cor. to Secs. 23, 24, 25 & 26, 20 ft. above toll road.	
	Thence I run, Var. 19°30' E.	
	W. on a true line bet. Secs. 23 & 26.	
40.00	Set basalt stone, 14 x 11 x 8 ins., 10 ins. in ground, for ¼ Sec. Cor., marked ¼ on N. face, from which,	
	A fir, 7 ins. diam., brs. N.23°E.,22 lks. dist., marked ¼ S., B.T.	
	A pine, 6 ins. diam., brs. S.30°E., 25 lks. dist., marked ¼ S., B.T.	
80.00	The Cor. to Secs., 22, 23, 26 & 27.	