

Subdivisional Lines, T. 1 S., R.36 E., W.M.

Chains		Feet
	Through scattering timber	
11.50	A wagon road, course E. & W.	
40.00	Set basalt stone, 10 x 9 x 6 ins., 7 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face, from which, A fir, 4 ins. diam., brs. S.30°E., 12 lks. dist., marked $\frac{1}{4}$ S., B.T. A fir, 5 ins. diam., brs. N.65°W., 11 lks. dist., marked $\frac{1}{4}$ S., B.T.	
70.00	Descend about 100 ft. to	
80.00	Set basalt stone, 14 x 12 x 6 ins., 9 ins. in ground, for Cor. to Secs., 25, 26, 35 & 36, marked with 1 notch on S. & E. edges, and raised a mound of stone alongside. Land; mountainous. Soil; sandy loam, 2nd rate. Timber; scattering fir, pine and tamarack.	
	E. on random line bet. Secs. 25 & 36. Var. 18 $\frac{1}{2}$ °E.	
	Descend about 400 ft. to	
18.00	Dry bed of creek, course N.W.	
40.00	Set temporary $\frac{1}{4}$ Sec. Cor.	
80.72	Intersect E. Bdy., 15 lks. N. of the Cor. to Secs. 25, 36, 30 & 31, which is a pine tree, 6 ins. diam., marked, T.1 S., S.30 on N.E. R.37 E., S.31 on S.E. R.36 E., S.36 on S.W. and S 25 on N.W. faces, with 1 notch on S. 1 notch on S. and 5 notches on N. edges, from which, A pine, 8 ins. diam., brs. N.63°W., 43 lks. dist., marked T.1 S., R.36 E., S.25, B.T. A pine, 18 ins. diam., brs. S.80°W., 43 lks. dist., marked T.1 S., R.36 E., S.36, B.T. A pine, 20 ins. diam., brs. S.34°E., 46 lks. dist., marked T.1 S., R.37 E., S.31, B.T. and a mound of stone alongside.	