

Subdivisional Lines, T.1 S., R.37 E., W.M.

Chains		Feet
	Thence I run	
	S.85°10'W. on true line bet. Secs. 1 & 12.	
40.40	Set basalt stone, 16 x 12 x 8 ins., 11 ins. in ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face, from which, A tamarack, 10 ins. diam., brs. N.62°W., 35 lks. dist., marked $\frac{1}{4}$ S., B.T. A tamarack, 6 ins. diam., brs. S.53°W., 12 lks. dist., marked $\frac{1}{4}$ S., B.T.	
80.80	The Cor. to Secs. 1, 2, 11 & 12. Sand; mountainous. Soil; 2nd rate. Heavy pine and fir timber. Dense pine and fir undergrowth.	
	N. bet. Secs. 1 & 2. Var. 22°30' E.	
1.00	Leave bottom and ascend hill.	
37.50	Ravine, course W., 1000 ft. above Sec. Cor.	
40.00	Set stone, 16 x 10 x 5 ins., 11 ins. in ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face and raised mound of stone alongside, in open glade. Pits impracticable.	
75.00	Top of ridge, brs. E. & W., 500 ft. above $\frac{1}{4}$ Sec. Cor. and descend.	
88.00	Intersect Base Line, 952 lks. E. of Stand. Cor. to Secs. 35 & 36. A basalt stone, 20 x 12 x 8 ins., marked B.L. with 1 notch on E. and 5 notches on W. edges, from which, A fir, 6 ins. diam., brs. N.7°E., 49 lks. dist., marked T.1 N., R.37 E., S.36, B.T. A fir, 22 ins. diam., brs. S.85°W., 21 lks. dist., marked T.1 S., R.37 E., S.2, B.T. A fir, 24 ins. diam., brs. N.45°W., 51 lks. dist., marked T.1 N., R.37 E., S.35, B.T.	
	Where set basalt stone, 16 x 8 x 8 ins., 11 ins. in ground for Closing Cor. to Secs. 1 & 2, marked C.C. with 1 notch on E. and 5 on W. and 6 notches on S. edges,	