

Subdivisions, T. 2, N., R. 36 E.

Chains	<p>June 25: At 7^h 40^m A. M., l. m. t., I set off 45° 40' on the lat. arc., 23° 25' N. on the decl. arc, and determine a true meridian with the solar at the cor. of secs. 11, 12, 13 and 14.</p>
	<p style="text-align: center;">Thence, I run S. 0° 01' E. on random line bet. secs. 13 and 14 .</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.24	<p>Intersect E. and W. line 1.45 chs. E. of the cor. of secs. 13, 14, 23 and 24, which is a basalt stone, 6 x 8 x 6 ins. above the ground, marked and witnessed as described by the Surveyor General.</p>
80.24	<p>Set basalt stone 20 x 10 x 6 ins., 15 ins. in the ground for closing cor. of secs. 13 and 14, marked with C.C. on N. face, and 3 notches on S. and 1 notch on E. edges, from which,</p> <p style="padding-left: 40px;">A fir, 30 ins. in diam. bears N. 33-3/4° E., 2.82 chs. dist., marked T.2 N., R. 36 E., S.13 B.T.</p> <p style="padding-left: 40px;">A fir, 28 ins. in diam., bears N.21° W., 1.09 chs. dist., marked T. 2 N., R. 36 E., S.14, B.T'</p> <p>I destroyed all marks on old cor. pertaining to the survey N. and took a new bearing on the S.</p> <p style="padding-left: 40px;">A fir, 20 ins. in diam., bears S.39° W., 3.21 chs. dist., marked T. 1 N., R.36 E., S. 23, B. T.</p> <p>Repaired stone mound.</p>
	<p>From the closing cor., I run, N. 0° 01' W. on true line bet. secs. 13 and 14. Pass along plateau on summit of ridge, through scattering timber.</p>
6.34	<p>A fir, 18 ins. in diam., on line, I mark with 2 notches on N. and S. edges.</p>
8.00	<p>Descend N. slope of hill, bears N. 35° W., S.70° E.</p>
29.00	<p>Ravine 75 ft. deep, course N. 30° E. Ascend gradually along W. slope of divide.</p>
37.05	<p>A white fir, 12 ins. in diam., on line, I mark with 2 notches on N. and S. edges.</p>