

Subdivisions, T. 2, N., R. 36 E.

Chains

- A fir, 10 ins. in diam., bears S. 20° E., 21 lks. dist., marked  $\frac{1}{4}$  S.15, B.T.
- A fir, 10 ins. in diam. bears S. 85° W., 36 lks. dist., marked  $\frac{1}{4}$  S. 16, B.T.
- This corner stands about 200 ft. below the top of ridge.
- 81.81 The cor. of secs. 9, 10, 15 and 16.  
Land, mountainous.  
Soil, stony and loam; 3rd and 2nd rate.  
Timber, fir, pine, spruce and tamarack.  
Mountainous land, 81.81 chs.
- 
- N. 0° 03' W. on true line bet. secs. 9 and 10.  
Descend gradually along E. slope of mountain through scattering timber.
- 5.80 Ravine, 100 ft. deep, course N. 80° E.
- 22.30 Spring branch, 5 lks. wide, course E.
- 40.00 Set basalt stone 20 x 14 x 4 ins., 15 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on W. face, from which  
A fir, 36 ins. in diam., bears S.20° E., 13 lks. dist., marked  $\frac{1}{4}$  S.10, B.T.  
A fir, 18 ins. in diam., bears N. 25° W., 98 lks. dist., marked  $\frac{1}{4}$  S. 9, B.T.
- 57.25 Ravine, 75 ft. deep, course E.
- 74.30 Stream, 5 lks. wide, swift current, course S. 80° E.
- 80.00 Set burnt stone 20 x 12 x 5 ins., 15 ins. in the ground for cor. of secs. 3, 4, 9 and 10, marked with 3 notches on E. and 5 notches on S. edges, from which  
A fir, 10 ins. in diam. bears N. 36° E., 80 lks. dist., marked T.2, N., R. 36 E., S.3, B.T.  
A fir, 22 ins. in diam. bears N. 11° W., 82 lks. dist., marked T.2, N., R. 36 E., S.4, B.T.  
No other trees in limits. Raise mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor. Pits impracticable.  
Land, mountainous.  
Soil, gravelly loam; 2nd rate.