

## Resurvey of East Bdy. of T. 2 N., R. 37 E.

Chains	
12.50	Top of ridge, 175 ft. above creek, bears N.60°W., S.60°E. Over rolling ground through dense forest.
38.50	Intersect old $\frac{1}{4}$ sec. cor., which is a post marked and witnessed as described by the surveyor general. I destroy all marks pertaining to the survey W.  Thence I run N.0°3'W.
40.00	Set an ironstone, 15x15x4 ins., 10 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face, from which, A fir, 30 ins. diam., bears S.14°W., 171 lks. dist., marked $\frac{1}{4}$ S 7 B T.
41.00	Top of ridge, 200 ft. high, bears E. and W.
41.50	Enter dense fir forest and undergrowth, bears E. and W.
43.00	Descend steep N. slope of hill.
74.15	Creek, in canyon, 300 ft. deep, 10 lks. wide, swift current, stony bottom, course N.60°W.
75.00	Ascend through scattering timber, bears E. and W.
77.96	Intersect old cor. of secs. 1, 6, 7 and 12, which is a post, entirely decayed, and witnessed as described by the surveyor general. I set a basalt stone, 15x12x10 ins., 10 ins. in the ground, at the same point for cor. of secs. 6 and 7 marked with 1 notch on the N. and 5 notches on the S. edges. I destroy all marks pertaining to the survey W.  Thence I run N.0°5'W.
80.00	Set an ironstone, 20x10x6 ins., 15 ins. in the ground, for cor. of secs. 1 and 12, marked with 1 notch on the N. and 5 notches on the S. edges, from which, A fir, 30 ins. diam., bears S.51°W., 109 lks. dist., marked T 2 N R 37 E S 12 B T.  A pine, 24 ins. diam., bears N.20°W., 115 lks. dist., marked T 2 N R 37 E S 1 B T.  This cor. stands about 100 ft. above the creek. Land, mountainous.