

Exterior & Subdivisional Lines, T. 2 S., R. 33 E., W.M.

Chains		Feet
	Land; mountainous & stony, 80.20 chs. Soil; 4th rate. Timber; pine, fir, tamarack & cottonwood in S. Canyon, 23.70 chs.	
	W. bet. Secs. 30 & 31. Descend. Var. 19°45'E.	
27.50	Enter timber.	
40.00	Set basalt stone, 20 x 6 x 5 ins., 15 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face. raised mound of stone, 2 ft. high x 4 $\frac{1}{2}$ ft. base over Cor., from which, A pine, 20 ins. diam., brs. S. 82°40' E., 178 lks. dist., marked $\frac{1}{4}$ S., B.T. A pine, 24 ins. diam., brs. N. 59° E., 148 lks. dist., marked $\frac{1}{4}$ S., B.T.	
42.00	Foot of descent.	
44.00	Pearson Creek, 15 lks. wide, course N. 15° W.	-700
100.00	Leave timber.	
106.25	Summit of ridge falls N. Descend 35°	+650
112.00	Enter timber.	
114.50	Canyon, course N. Ascend 32°	-800
132.10	Summit. Descend.	
137.60	Intersect W. Bdy. of Tp., 500 lks. S. of Cor. to Secs. 25, 30, 31 & 36, which is a basalt stone, 18 x 12 x 6 ins., 8 ins. in ground, marked 5 notches on N. Cor. I cut 1 notch on S. edge and raised mound of stone, 2 ft. high x 3 $\frac{1}{2}$ ft. base over Cor. Var. 17°00'E.	
	At point of intersection, I Set basalt stone, 12 x 8 x 6 ins., 8 ins. in ground, for Closing Cor. to Secs. 30 & 31, marked 5 notches on N. Cor., 1 notch on S. Cor., C.C. on W. face. Raised mound of stone, 2 ft. high x 3 $\frac{1}{2}$ ft. base over Cor., from which, A fir, 12 ins. diam., brs. N. 20° E., 33 lks. dist., marked T. 2 S., R. 33 E., S. 30, B.T. A pine, 36 ins. diam., brs. S. 40° E., 62 lks. dist., marked T. 2 S., R. 33 E., S. 31, B.T. on W. face of Mt.	