

Re-survey Subdivisional Lines, T.2 S., R.34 E., W. M.

Chains		Feet
21.30	Descend broken N.E. slope, 750 ft. to Johnson Creek, 25 lks. wide, course N.30°E., enter narrow bottom.	
24.30	Leave bottom, brs. N.30°E. & S.30°W., ascend S.W. slope.	
28.00	Leave timber, brs. N.E. & S.W.	
33.75	Dry gulch, course S.60°W., ascend 414 ft. to	
40.00	Set iron post, 3 ft. long, 1 in. diam., 26 ins. in ground, for $\frac{1}{4}$ Sec. Cor., with brass cap, marked	
	$\begin{array}{c} \frac{1}{4} \\ S10 S11 \\ 1917 \end{array}$	
	from which,	
	A cross on face of cliff, 15 ft. high, $1\frac{1}{2}$ ft. face, facing S.W., brs. N.19°E., 153 lks. dist., marked $\frac{1}{4}$ 11, B.O., chiseled beside the cross; marks 2 ft. above base of cliff.	
	Raise mound of stone, 3 ft. base, 2 ft. high, W. of Cor.	
	Ascend on irregular S.W. slope, 520 ft. to	
67.50	Top of ridge, brs. N.W. & S.E., descend 250 ft. to Sec. Cor.	
70.75	Enter timber & brush, brs. N.W. & S.E.	
80.00	Set iron post, 3 ft. long, 2 ins. diam., 24 ins. in ground, for Cor. of Secs. 2, 3, 10 & 11, with brass cap marked	
	$\begin{array}{c} T2S R34E \\ S3 S2 \\ \hline S10 S11 \\ 1917 \end{array}$	
	from which,	
	A fir, 10 ins. diam., brs. N.15°45'E., 59 lks. dist., marked T.2 S., R.34 E., S.2, B.T.	
	A fir, 6 ins. diam., brs. S.73°E., $38\frac{1}{2}$ lks. dist., marked T.2 S., R.34 E., S.11, B.T.	
	A fir, 8 ins. diam., brs. S.80°W., 22 lks. dist., marked T.2 S., R.34 E., S.10, B.T.	
	A fir, 8 ins. diam., brs. N.10°W., 37 lks. dist., marked T.2 S., R.34 E., S.3, B.T.	
	Land; mountainous.	
	Soil; rocky with scant loam, 3rd rate.	
	Timber; pine & fir.	
	Undergrowth; fir, pine, willow & ninebark.	