

Township 3 N., R. 37 E., W.M.

Chains	a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high N.E. of Cor., the most secure plan. Pits impracticable.
40.11	A point 300 ft. above the closing Sec. Cor. and a rock in place, 24 x 18 x 16 ins. above ground, on which I cut a cross (X) at the exact Cor. pt. for $\frac{1}{4}$ Sec. Cor., N. Bdy. of Sec. 22, marked $\frac{1}{4}$ on S. face and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of Cor. Pits impracticable.
76.50	Descend along steep rocky side of river canyon.
79.99	Ravine, course S. The Cor. of Secs. 14 & 15, whence the closing Cor. of Secs. 22 & 23, established August 8, 1900, an iron-stone, 10 x 10 x 5 ins. above ground, marked and witnessed as described in the field notes of survey of subdivisions returned to the Surveyor-General, bears S. 89° 34' E., 1 ch. 13 lks. dist., Land; mountainous. Soil; stony, 4th rate. Timber; widely scattering pine and fir. Undergrowth; pine, fir, alder, willow and bunchgrass. Good grazing land. Mountainous land, 79.99 chs.
	August 16, 1900
	S. 89° 45' W., on a blank line, S. Bdy. of Sec. 16; at 39.10 chs. set temp. $\frac{1}{4}$ Sec. Cor., N. Bdy. Sec. 21 in river's edge; at 40.18 chs. fail to find any trace of the old $\frac{1}{4}$ Sec. Cor.; set temp. Cor., at 79.22 chs. intersect temp. closing Cor. of Secs. 20 & 21; and at 80.11 chs. intersect the Cor. of Secs. 16 & 17, which is a Basalt Stone, 16 x 12 x 7 ins. on N.W. face of Spur, marked and witnessed as described by the Surveyor-General.
	Thence I run N. 89° 45' E., on a true line, S. Bdy. of Sec. 16. Descending steep, irregular N. face of mountain, thru heavy timber and undergrowth; bears N. 70° W. & S. 70° E.