

Exterior Lines, T.3 S.,R.31 E.,W. M.

Chains		Feet
	S. on E. Bdy. of Sec. 36.	
	Var.19°30'E.	
40.00	Set stone, 16 x 10 x 8 on S.W. slope of knoll, for $\frac{1}{4}$ Sec. Cor.	
	A pine, 8 ins. diam.,brs. S.88°E., 98 lks. dist.	
	A pine, 12 ins. diam.,brs. N.54°W., 48 lks. dist.	
80.00	Settstone, 18 x 14 x 5, on nearly level ground for Cor. to Tps.3 & 4 S.,Rs.31 & 32 E., from which,	
	A tamarack, 12 ins. diam.,brs. N.26°E., 20 lks. dist.	
	A pine, 12 ins. diam.,brs. S.48°E., 46 lks. dist.	
	A pine, 12 ins. diam.,brs. S.54°W., 40 lks. dist.	
	A fir, 6 ins. diam.,brs. N.42°W., 10 lks. dist.	
	Land; surface rolling.	
	Soil; 2nd rate.	
	Good timber; pine, fir & tamarack.	
	Nov. 7, 1878.	
	From the Cor. to Tps. 3 & 4 S.,Rs. 31 & 32 E.,I run	
	W. on random line along S. Bdys. Secs. 36, 35, 34, 33, 32 and 31.	
	Var.19°15'E.	
	I set $\frac{1}{2}$ mile & mile posts at every 40.00 & 80.00 chs.,& at 6 miles, 1 ch. & 28 lks., I	
	Intersect W. Bdy., 68 lks. N. of Cor. to Tps. 3 & 4 S.,Rs. 30 $\frac{1}{2}$ & 31 E., making my correction, 11 $\frac{1}{3}$ lks. S. per mile.	
	From the Cor. to Tps. 3 & 4 E.,Rs. 30 $\frac{1}{2}$ & 31 E.,I run	
	N.89°55' E. on true line, along S. Bdy. of Sec. 31.	
	Var. 21°45'E.	
4.50	Spring branch, course N.	
18.00	Summit of ridge,N.E. & S.W.	200
41.28	Set stone, 17 x 12 x 6 on E. hillside, for $\frac{1}{4}$ Sec. Cor.	
	A pine, 12 ins. diam.,brs. S.20°E.,41 lks. dist.	
	A pine, 14 ins. diam.,brs. N.20°E., 54 lks. dist.	
	Spring branch, course S.	200
81.28	Set stone, 15 x 10 x 4 on S.W. hillside for Cor. to Secs. 31, 32, 5 & 6, from which,	50