

Subdivisional Lines, T.3 S.,R.33 E.,W. M.  
 As surveyed by Rufus S. Moore, U.S.Deputy Surveyor,  
 Under Contract No. 451,  
 Dated June 12, 1882.

Chains		Feet
	From the Cor. to Secs. 2, 3, 34 & 35, on S. Bdy. of Tp., which is a basalt stone, 16 x 10 x 5 ins., set firmly in ground, marked with 2 notches on E. & 4 notches on W. edges, with mound of stone alongside, from which, A pine, 24 ins. diam., brs. S.21°E., 136 lks. dist., marked T.4 S.,R.33 E.,S.2,B.T. A pine, 10 ins. diam., brs. S.51°W., 89 lks. dist., marked T.4 S.,R.33 E.,S.3,B.T. A pine, 8 ins. diam., brs. N.69°W., 68 lks. dist., marked T.3 S.,R.33 E.,S.34,B.T.	
	I ran	
	N. bet. Secs. 34 & 35. Var.24°E. Ascend	
12.00	Top of hill, brs. E. & W., 150 ft. above Sec. Cor.	
40.00	Set basalt stone, 18 x 15 x 5 ins., 12 ins. in ground, for Sec. Cor., marked $\frac{1}{4}$ on W. face, from which, A pine, 7 ins. diam., brs. N.48°E., 15 lks. dist., marked $\frac{1}{4}$ S.,B.T. A pine, 18 ins. diam., brs. S.53°W., 49 lks. dist., marked $\frac{1}{4}$ S.,B.T.	
55.00	Descend hill, brs. N.W. & S.E.	
80.00	Set basalt stone, 18 x 15 x 6 ins., 12 ins. in ground, for Cor. to Secs. 26,27,34 & 35, marked with 1 notch on S. and 2 on E. edges & raised mound of stone alongside, from which, A pine, 18 ins. diam., brs. N.40°E., 133 lks. dist., marked T.3 S.,S.26,B.T. A pine, 4 ins. diam., brs. N.40°W., 44 lks. dist., marked R.33 E.,S.27,B.T. A pine, 7 ins. diam., brs. S.73°W., 57 lks. dist., marked S.34,B.T.	
	No tree convenient on S.E.	
	Land; rolling hills. Soil; 2nd rate.	
	Heavily timbered with pine, & fir; dense undergrowth of pine & fir.	
	*****	
	N. bet. Secs. 26 & 27. Var.24° 30'E.	
	Descend.	