

1st Standard Parallel N. R. 28, E. W.M.

Chains		Feet
	Course of down River N., 10 W. Course of up River S. 40° E.	
46.17	Left bank of river, very rapid, not navigable. Distance over river, 303 lks. by measurement.	
80.00	Set post for Cor. to Secs. 32 & 33, in mound of earth, trench and pits as per instructions. Soil; in bottom 1st rate, balance sand and gravel, on bank of river are a few small willows, small sage, greasewood, and scattering grass, $\frac{1}{2}$ of the ground covered with cactus.	
	W. on S. Bdy. of Sec. 32	
		Var. 18° E.
40.00	Set post for $\frac{1}{4}$ Sec. Cor. in mound of earth, trench & pits as per instructions.	
-80.00	Set post for Cor. to Secs., 31 & 32 in mound of earth, trench and pits as per instructions. Soil; sand and gravel, grass poor, sage scattering and small. Land; ascend to the W.	
	W. on S. Bdy. of Sec. 31	
		Var. 18° E.
40.00	Set post for $\frac{1}{4}$ Sec. Cor. in mound of earth, trench, and pits as per instructions.	
80.00	Set post for Cor. to Tps. 5 N., Rs. 27 & 28 E., in mound of earth, trench and pits as per instructions. Soil; sand and gravel, gently rolling, covered with sage, cactus and scattering grass.	
		May 6, 1860
	Remeasurements of N. Bdy. of T. 4 N., R. 28 E., W.M. As surveyed by Ebenezer E. Haft, U.S. Deputy Surveyors. Under Contract No. 93 Dated September 11, 1860.	
	The N. Bdy. of T. 4 N., of R. No. 28 E., of the W.M. on the 1st Standard Parallel N.	