

Subdivisional Lines of T. 4 N., R. 37 E., W.M.

Chains		Feet
	N. bet. Secs. 20 & 21	
	Var. 20° 00' E.	
	Along down N.E. face of bluff	
40.00	In bed of creek, I offset N., 50 lks. and set basalt stone 20 x 10 x 5 in creek bottom for $\frac{1}{4}$ Sec. Cor. A fir, 10 ins. diam. brs. N. 20° E., 10 lks. dist. A Maple, 4 ins. diam. brs. N. 85° W., 25 lks. dist.	
43.00	Steep open hillside.	
65.00	Enter timber, course N.W. and S.E.	
80.00	Set tamarack on N. slope, for Cor. to Secs. 16, 17, 20 & 21 A fir, 8 ins. diam. brs. N. 38° E., 35 lks. dist. A fir, 10 ins. diam. brs. S. 56° E., 20 lks. dist. A fir, 18 ins. diam. brs. S. 42° W., 13 lks. dist. A fir, 10 ins. diam. brs. N. 68° W., 20 lks. dist. Land; surface, mountainous Soil; 3rd rate. Timber; mostly scattering, some heavy timber on creek, fir, tamarack and pine, good grass on open ground. Aug. 26.	
	E. on a random line bet. Secs. 16 & 21	
	Var. 20° 00' E.	
40.00	Set post for temp. $\frac{1}{4}$ Sec. Cor.	
82.30	Intersected N. & S. line, 328 lks. S. of Cor. to Secs. 15, 16, 21 & 22, from which Cor. I run S. 87° 40' W. on a true line bet. Secs. 16 & 21	
40.00	Var. 20° 00' E.	
2.50	Spring branch, course N.E.	
17.00	On bluff, course N.W. and S.E., also wagon road to Walla Walla, N.W.	
35.00	Cabin and spring, about 4 chs. N.	
40.00	Set Tamarack post on N. slope for $\frac{1}{4}$ Sec. Cor. A Tamarack, 6 ins. diam. brs. N. 50° W., 29 lks. dist. A Tamarack, 7 ins. diam. brs. S 24° W., 45 lks. dist.	