

Subdivisional Lines of T. 4 N., R. 37 E., W.M.

Chains		Feet
	<p>June 15: Thence I run N. 0° 01' W. bet. Secs. 11 and 12, on random Ascend steep S. slope</p>	
40.00	Set temp. $\frac{1}{4}$ Sec. Cor.	
79.94	Intersect E. and W. line, 30 lks. E. of the Cor. of Secs. 1, 2, 11 & 12, which is a post, 4 ins. sq., $1\frac{1}{2}$ ft. above ground, marked and witnessed or described by the surveyor general.	
	<p>Thence I run S. 0° 14' E. on a true line bet. Secs. 11 and 12. Descend S.W. slope of mountain, through scattering timber</p>	
5.25	Leave timber, brs. E. and W.	
19.00	Descend steep S. slope of mountain into Walla Walla Canyon.	
40.00	Set an ironstone, 15 x 10 x 8 ins. in mound of stone, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on the W. face, raise mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, S.W. of Cor.; this being the most secure place. Pits impracticable.	
	Thence descend steep S. slope over small ridges and ravines	
70.00	Ridge point, brs. N.W. and S.E. Descend over bluffs and sliders.	
79.94	The Cor. of Secs. 11, 12, 13 & 14. Land; mountainous Soil; stony, 4th rate. Timber, scattering fir and pine, Mountainous land, 79.24 chs. At this Sec. Cor. I set off 23° 15' on the decl. arc; & at 12th ^{A M} 00 A.M. l.m.t. observe the sun on the meridian, the resulting lat. is 45° 50', which is 0' 3 less than the proper lat.	
	<p>The Cor. of Secs. 14, 15, 22 & 23, which is a post, 4 ins. sq., marked as per instructions., instead of a basalt stone as stated by the Surveyor General, from which A pine, 24 ins. diam. brs. N. 37° E., 284 lks. dist. marked T 4 N., R. 37 E., S. 14 B.T.</p>	