

## Resurvey of Exterior Bdy. of T 4 N., R 38 E., W.M. (N. Bdy.)

Chains		Feet
	S. 89° 57' E. on S. Bdy. of Sec. 31 Gradually ascending through heavy timber.	
.80	Trail, brs. N. 50° E., and S. 50° W., descend gradually.	
13.50	Leave timber, brs. S. 60° E., and N. 10° W., thence steep descent.	
28.00	Bottom of ravine, 150 ft. deep, course S. 30° E., ascend	
33.40	Top of <del>rise, desc.</del> steep hill, brs. N. & S., difference bet. measurement of 40.00 Chs. by two sets of chainmen is 8 lks.; position of middle point by first set is 39.96 chs. By 2nd B.T. 40.04 Chs. the mean of which	
40.00	After renewed search find no trace of the <sup>old</sup> standard $\frac{1}{4}$ Sec. Cor. described by the surveyor general in a basalt stone, 16 x 14 x 6 ins.  I set a basalt stone, 20 x 10 x 6 ins., 15 ins. in the ground for standard $\frac{1}{4}$ Sec. Cor., marked S 6 $\frac{1}{4}$ on N. face and raised a mound of stone 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of Cor.; pits impracticable	
40.35	Ravine, course S.; ascend	
41.50	Top of ridge, brs. N. and S. descend	
43.00	Ravine, 100 ft. deep, course S.; ascend S. slope	
65.00	Ridge, brs. N. 10° E. and S. 10° W.; descend through timber.	
72.00	Leave timber, brs. N. 30° E. and S. 30° W.	
76.75	More gradual descent.	
77.75	Dry bed of stream, 25 lks. wide, course S.W.  A point 1,000 ft. below the T., Cor. and find no trace of the old Standard Cor. of Secs. 31 and 32, described by the surveyor general as a basalt stone, 16 x 10 x 6 ins. from which  A fir, 10 ins. diam. brs. N. 85° E., 340 lks. dist. Difference bet. measurement of 80.00 Chs. by two sets of chainmen is, 12 lks.; position of middle point: By 1st set: 80.06 Chs. By 2nd set: 79.84 Chs.; the mean of which is	
80.00	Set an ironstone, 22 x 12 x 4 ins. 16 $\frac{1}{2}$ ins. in the ground, for standard Cor. of Secs. 31 & 32, marked S. 6 on N. face; with 5 grooves on E. and 1 groove on W faces; and	