

## Resurvey of Exterior Bdy. of T 4 N., R. 38 E., W.M. (N. Bdy.)

Chains		Feet
80.00	<p>the surveyor general, brs. S. <math>7\frac{1}{2}</math> lks. dist. I destroy all trace of this old Cor.</p> <p>A point, 200 ft. below the last Sec. Cor. and difference in measurement of 80.00 Chs. by two sets of chainmen is 20 lks.; position of middle point:</p> <p>By 1st set, 79.90 Chs.</p> <p>By 2nd set, 80.10 Chs.; the mean of which is</p> <p>Set a basalt stone, 20 x 10 x 12 ins. 15 ins. in the ground for standard Cor. of Secs. 35 &amp; 36, marked S. 6 in N. face, with 1 groove on E. and 5 grooves in W. faces, from which,</p> <p style="padding-left: 40px;">A pine, 18 ins. diam. brs. N. <math>5^{\circ}</math> E., 59 lks. dist. Marked T 5 N., R. 38 E., S. 36, B.T.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam. brs. N. <math>2^{\circ}</math> W., 60 lks. dist. Marked T. 5 N., R. 38 E., S. 35, B.T.</p> <p>Land; mountainous</p> <p>Soil; stony, 4th rate.</p> <p>Timber; scattering pine, fir and tamarack</p> <p>Undergrowth, pine, fir, tamarack, chapparal, and bunchgrass</p> <p>Mountainous land; 80.00 Chs.</p>	
35.25	<p>S. <math>89^{\circ} 57'</math> E. on S. Bdy. of Sec. 36</p> <p>Ascending through scattering timber, hill brs. N.W. &amp; S.E.</p> <p>The old standard <math>\frac{1}{4}</math> Sec. Cor., a basalt stone, 18 x 10 x 5 ins. marked and witnessed as described by the surveyor general, brs. S. 3 lks. dist. I destroy all traces of this old <math>\frac{1}{4}</math> Sec. Cor. Difference in measurement of 40.00 Chs. by two sets of chainmen is 6 lks.; position of middle point:</p> <p>By 1st set, 39.97 Chs.</p> <p>By 2nd set, 40.03 Chs.; the mean of which is</p>	
40.00	<p>Set an iron stone 20 x 8 x 5 ins., 15 ins. in mound of stone on rocky ground, from standard <math>\frac{1}{4}</math> Sec. Cor. from which:</p> <p style="padding-left: 40px;">A pine, 15 ins. diam. brs. N. <math>88^{\circ}</math> E., 2 Chs. and 10 lks. dist., marked <math>\frac{1}{4}</math> S. 36 B.T.</p>	