

Subdivisional Lines of T 4 N R 38 E., W.M.

Chains		Feet
	<p>marked T 4 N R 38 E S 11 B T</p> <p>A fir, 20 ins. diam. brs. N. 25° W., 24 lks. dist.</p> <p>marked T 4 N R 38 E S 2 B T</p> <p>Land; mountainous</p> <p>Soil; 1st and 2nd rates.</p> <p>Timber, fir, pine, spruce</p> <p>Undergrowth; willow, maple and wild berry</p> <p>Mountainous or heavily timbered land or land covered with dense undergrowth and exceptionally difficult to survey.</p> <p style="text-align: right;">80.00 Chs.</p>	
	<hr/>	
	<p>N. on a sectional guide meridian bet. Secs. 1 & 2.</p> <p>Descend through scattering timber and dense undergrowth.</p>	
8.50	A creek, 5 lks. wide, brs. N. 10° W	
28.40	Foot of descent, 2000 ft. below top of divide.	
	Thence over river bottom	
33.25	Walla Walla River, 50 lks. wide, course S. 40° W.	
	Cold, clear water flowing over stony bed.	
35.00	Leave river bottom, brs. E. and W. and begin steep ascent	
40.00	Set a basalt stone, 15 x 8 x 5 ins., 10 ins. in the ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face; from which	
	<p>A fir, 12 ins. diam. brs. S. 65° E., 15 lks. dist.</p> <p>marked $\frac{1}{4}$ S 1 B T</p> <p>A fir, 8 ins. diam. brs. N. 67° W., 21 lks. dist.</p> <p>marked $\frac{1}{4}$ S 2 B T</p>	
43.50	Summit of spur, 75 ft. high, brs. N. 20° E. and S., 20° W.	
80.00	Intersect the first standard parallel N. 14.30 Chs. N. 89° 28' W. of the standard Cor. to Secs. 35 & 36, which is a basalt stone, 15 x 18 x 12 ins. above ground, marked and witnessed as described by the surveyor general.	
	At the point of intersection with the first standard parallel N. I set a basalt stone, 15 x 5 x 5 ins., 10 ins. in the ground for Closing Cor. to Secs. 1 & 2, marked C C on S.; with 1 groove on E. and 5 grooves on W. face; from which,	