

## Exterior Lines of T. 4 S., R. 29 E. W.M.

Chains	Feet
	<p>A Pine 30 ins. diam. brs. N. 45° E. 47 lks. dist. marked T. 4 S., R. 30 E., S. 18 B.T.</p> <p>A Tamarack 9 ins. diam. brs. S. 12° E., 40 lks. dist. marked T. 4 S., R. 30 E., S. 19 B.T.</p> <p>A Pine 14 ins. diam. brs. S. 42° W. 34 lks. dist., marked T. 4 S., R. 29 E., S. 24 B.T.</p> <p>A Tamarack 9 ins. diam. brs. N. 10° W. 38 lks. dist., marked 4 S., R. 29EE., S. 13 B.T.</p> <p>Descent about 300 ft.</p> <p>Land; surface N. 50.00 chs., mountainous, S. 29.50 chs. nearly level,</p> <p>Soil; 3rd rate, some Pine, Tamarack and Fir timber, but mostly open or scattering.</p>
	N. bet. Secs. 13 and 18.
	Var. 20° 15' E.
27.00	A brook, 4 lks. wide, course N.W., descent 100 ft.
40.00	Set a basalt stone 12 x 10 x 7 ins. 8 ins. in ground for $\frac{1}{4}$ Sec. Cor. on N.W. slope, marked $\frac{1}{4}$ on W. face, from which, A Tamarack 20 ins. diam. brs. N. 62° E. 16 lks. dist. marked $\frac{1}{4}$ S.B.T. A Tamarack 20 ins. diam. brs. N. 34° W. 26 lks. dist. marked $\frac{1}{4}$ S.B.T.
80.00	A Pine 9 ins. diam. on N.W. slope for Cor. to Secs. 12, 13, 7 and 18,, marked T. 4 S., S. 7 on N. marked T. 4 S., S. 7 on N.E. R. 30 E., S. 18 on S.E. T. 4 S., S. 13 on S.W., and R. 29 E., S. 12 on N.W., faces with 2 notches notches on N. and 4 notches on S. faces from which, A Pine 8 ins. diam. brs. N. 38° E. 55 lks. dist., marked T. 4 S., R. 30 E., S. 7 B.T. A Pine 30 ins. diam. brs. S. 64° E. 26 lks. dist., marked T. 4 S., R. 30 E. S. 18 B.T. A Tamarack 18 ins. diam. brs. S. 60° W. 30 lks. dist.,