

Subdivisional Lines of T. 4 S., R. 30 E. W.M.

Chains		Feet
	N. bet, Sec. 22 and 23, Var. 20° 00' E.	
26.50	A brook, 4 lks. wide, course S.E. Descent about 100 ft.	
40.00	Set a basalt stone 17 x 8 x 7 ins. 12 ins. in ground on slight S. slope for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face. No trees, Raised mound of stone alongside in lieu of pits.	
46.50	Wagon Road, course S.E. and N.W.	
80.00	Set a basalt stone 17 x 12 x 5 ins., 12 ins. in ground on N. slope for Cor. to Secs. 14, 15, 22 and 23. Marked with three notches on S. and 2 notches on E. edges. A Tamarack 12 ins. diam. brs. N. 55° E. 62 lks. dist. marked T. 4 S., R. 30 E., S. 14 B.T. A Fir 10 ins. diam. brs. S. 48° E. 40 lks. dist. marked T. 4 S., R. 30 E., S. 23 B.T. A Tamarack 14 ins. diam. brs. S. 70° W. 11 lks. dist. marked T. 4 S., R. 30 E., S. 22 B.T. A Fir 12 ins. diam. brs. N. 42 W. 17 lks. dist. marked T. 4 S., R. 30 E., S. 15 B.T. Ascent about 120 ft. Land; surface rolling, Soil; 3rd and 2nd rate, Pine, Tamarack and Fir. Timber thick in places, but mostly open, with some open glades.	
	E. on a random line bet. Secs. 14 and 23. Var. 20° 45' E.	
	Descending,	
40.00	Set temp. $\frac{1}{4}$ Sec. Cor.	
80.28	Intersected N. and S. line, 46 lks. S. of Cor. to Secs. 13, 14, 23 and 24 from which Cor. I run, S. 89° 40' W. on a true line bet. Sec. 14 and 23. Var. 21° 00' E.	
40.14	Set a basalt stone 12 x 10 x 8 ins., 8 ins. in ground on E. slope for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face.	