

## Subdivisional Lines of T. 4 S., R. 30 E., W.M.

Chains		Feet
	<p>A Pine 20 ins. diam. brs. S. 75° W. 48 lks. dist. marked <math>\frac{1}{4}</math> S. B.T.</p>	
78.42	<p>The Cor. to Secs. 19, 20, 29 and 30. Land; surface undulating, Soil; 2nd and 3rd rate, scattering Pine, tamarack and Fir timber with open glades.</p>	
	<p>N. bet. Secs. 19 and 20, Var. 23° 30' E.</p>	
24.50	Wagon road, course E. and W.	
30.00	Begin steep descent	
40.00	<p>Set a post 4 ft. long 4 ins. diam. on steep N. slope for <math>\frac{1}{4}</math> Sec. Cor., marked <math>\frac{1}{4}</math> S. on W. face. A Fir 6 ins. diam. brs. S. 15° E. 29 lks. dist. marked <math>\frac{1}{4}</math> S. B.T. A Tamarack 10 ins. diam. brs. N. 24° W. 21 lks. dist.</p>	
47.00	A ravine and spring branch, course N.W., descent about 250 ft.	
80.00	<p>Set a basalt stone 18 x 12 x 10 ins. 12 ins. in ground on steep S.W. slope for Cor. to Secs. 17, 18, 19 and 20, marked with three notches on S. and 5 notches on E. edges. Ascent about 150 ft. A Pine 8 ins. diam. brs. N. 66° E. 95 lks. dist. marked T. 4 S., R. 30 E., S. 17 B.T. A Pine 28 ins. diam. brs. S. 28° E. 40 lks. dist. marked T. 4 S., R. 30 E., S. 20 B.T. A Pine 20 ins. diam. brs. S. 21° W. 64 lks. dist. marked T. 4 S., R. 30 E., S. 19 B.T. A Pine 28 ins. diam. brs. N. 56° W. 30 lks. dist. marked T. 4 S., R. 30 E., S. 18 B.T.</p>	
	<p>Land; surface S. 30 Chs undulating, N. 5 Chs. mountainous, Soil; 3rd and 2nd rate, S. 30 Chs. scattering and N. 50 Chs heavily timbered Pine, Tamarack and Fir. Some open glades.</p>	