

## Retracement W. Bdy., T 5 N R 38 E W M.

Chains	Over gently rolling ground through heavy timber.
13.50	Old logging road; brs. N.60°E. & S.60°W.
19.50	Old logging road; brs. N.40°W. & S.40°E.
40.00	The $\frac{1}{4}$ Sec. Cor., a post marked & witnessed, as described by the Surveyor General.
	Thence I run
	N.0°56' E., bet. Secs. 31 & 36.
	Descending N. slope.
50.00	Steeper descent; dense undergrowth.
51.50	Spring,
79.75	A point, 500 ft. below Tp. Cor. & Cor. of Secs. 25, 30, 31 and 36, a post, marked & witnessed as described by the Surveyor General.
	Land; gently rolling & hilly.
	Soil; part arable, light & gravelly loam, 2nd, 3rd & 4th rates.
	Heavily timbered with pine, fir & tamarack.
	Undergrowth; pine, fir, tamarack, chaparral, huckleberry, willow & bunch grass.
	Heavily timbered land, 79.75 chs.
	N.1°20' W. on W. Bdy. Sec. 30.
	Descending through heavy timber & dense undergrowth; hill brs. N.E. & S.W.
30.00	Enter scattering timber.
40.00	A point, 650 ft. below the Sec. Cor. and set a basalt stone, 20 x 10 x 6 ins., 15 ins. in ground, for $\frac{1}{4}$ Sec. Cor., W. Bdy. of Sec. 30, marked $\frac{1}{4}$ on W. face; and raise mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of Cor. Pits impracticable.
45.00	Steeper descent through heavy timber, brs. E. & W.
80.00	A point, 1000 ft. below $\frac{1}{4}$ Sec. Cor. and set an ironstone, 18 x 16 x 12 ins., 13 $\frac{1}{2}$ ins. in ground, for Cor. of Secs. 19 & 30, marked with 4 notches on N. and 2 notches on S. edges; from which