

Resurvey part of N. Bdy., T 5 N R 38 E W M.

Chains.

- Ascending gradually through heavy timber and undergrowth.
- 18.22 The Cor. of Secs. 35 & 36, a post in mound of stone, marked and witnessed, as described by the Surveyor General.
- Thence I run
- S.89°46' W. along line of old blazes; steep slope northward.
- 40.11 Set fir post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for $\frac{1}{4}$ Sec. Cor., N. Bdy. of Sec.1, marked $\frac{1}{4}$ S on N. face; from which
- A fir, 10 ins. diam., brs. N.25°E., 29 lks. dist., marked $\frac{1}{4}$ S 1 B T.
- A fir, 6 ins. diam., brs. S.20°W., 11 lks. dist., marked $\frac{1}{4}$ S 1 B T.
- Note; The witness tree N. of line was deemed more permanent.
- Descend along " breaks" of Mill Creek canyon.
- 80.22 A point, 500 ft. below the $\frac{1}{4}$ Sec. Cor. and the temp. Closing Cor. of Secs. 1 & 2, a fir post established as true Cor., as described on pg. 37.
- Land; mountainous.
- Soil; gravelly & stony, 3rd & 4th rates.
- Heavily timbered with pine, fir, tamarack & spruce.
- Undergrowth; pine, fir, tamarack, spruce, alder, willow, huckleberry, pine & bunch grass.
- Mountainous & heavily timbered land, 80.22 chs.
- July 28, 1899.

Exterior Lines, T 5 N R 39 E W M.
As surveyed by Rufus S. Moore, U.S. Deputy Surveyor,
Under Contract No. 437,
Dated June 3rd, 1882.

From the Standard Cor. to Tps. 5 N., Rs. 38 & 39 E., which is a basalt stone, 18 x 15 x 12 ins., 12 ins. in ground, marked SC on N., with 6 notches on N., S., E. & W. edges; from which

A fir, 5 ins. diam., brs. N.35°E., 32 lks. dist., marked T 5 N R 39 E S 31 B T.

A pine, 22 ins. diam., brs. N.43°W., 13 lks. dist.,