

## Exterior Lines, T 5 N R 39 E W M.

## Chains

C.C. on S., R 39 E S 6 on E. and R 38 E S 1 on W. faces with 6 notches on E., S. and W. faces; from which

A spruce, 8 ins. diam., brs. N.24°W., 11 lks. dist., marked T 6 N R 38 E S 36 B T.

A spruce, 6 ins. diam., brs. S.65°W., 6 lks. dist., marked T 5 N R 38 E S 1 B T.

A spruce, 8 ins. diam., brs. S.68°E., 6 lks. dist., marked T 5 N R 39 E S 6 B T.

Land; broken & mountainous.

Soil; 2nd & 3rd rate.

Heavily timbered with spruce, fir and tamarack.

Dense undergrowth of spruce, fir & hemlock.

Aug. 5th, 1882.

Resurvey E Bdy., T 5 N R 38 E W M.,  
As surveyed by Geo. R. & Wm. E. Campbell, U.S. Deputy Surveyors,  
Under joint Contract No. 699 & Special Instructions,  
Dated Mar. 23, 1899.

Preliminary to commencing the subdivision of this Tp., I run N. on blank line on E. Bdy. of Sec. 36 and at 40 chs. intersect the  $\frac{1}{4}$  Sec. Cor., at 80.00 chs. fail to find any trace of the Cor. of Secs. 25, 30, 31 & 36; I set temp. Sec. Cor. and at 81.50 chs., fall 15 lks. W. of old Cor. of Secs. 25, 30, 31 & 36. Therefore I continue my line N., find this E. Bdy. very nearly correct in alignment, but out of limit in its measurement and a portion of the Cors. thereon partially, or wholly obliterated; and

At 6 miles, 13 chs. and 47 lks., I intersect the Closing Cor. of T 5 N Rs. 38 & 39 E. As these Tps. have not been subdivided, in accordance with the Manual & supplemental special instructions received from the Surveyor General, I resurvey the range line bet. them, as follows:

The Standard Cor. of T. 5 N., Rs. 38 & 39 E., is a pine, 32 ins. diam., marked & witnessed as described by the Sur-  
*July 20*