

## Resurvey E. Bdy., T 5 N R 38 E W M.

## Chains

N. bet. Secs. 19 & 24.

Ascending steep, bluffy mountain through scattering timber;  
brs. N.W. & S.E.

40.00 No  $\frac{1}{4}$  Sec. Cor. was established on E. Bdy. of Sec. 24 at the  
time of original survey;

I set an ironstone, 15 x 12 x 5 ins., 10 ins. in ground, for  
 $\frac{1}{4}$  Sec. Cor., marked  $\frac{1}{4}$  on W. face and raise mound of stone  
2 ft. base,  $1\frac{1}{2}$  ft. high, W. of Cor. Pits impracticable.  
Sky overcast at 12 M.; observation for Lat. not possible.

July 20, 1899.

July 21: At 7 h. 16 m., A.M., l.m.t., I set off  $45^{\circ} 54'$   
on the lat. arc;  $20^{\circ} 26'$  N. on the decl. arc; and deter-  
mine a true meridian by the solar at this  $\frac{1}{4}$  Sec. Cor.

80.00 At point, 2800 ft. above the last Sec. Cor. and

Set basalt stone, 24 x 16 x 12 ins., 18 ins. in ground, for  
Cor. to Secs. 13, 18, 19 & 24, marked with 3 notches on  
N. and S. edges; from which

A fir, 28 ins. diam., brs. N.  $75^{\circ}$  E., 23 lks. dist.,  
marked T 5 N R 39 E S 18 B T.

A fir, 40 ins. diam., brs. S.  $20^{\circ}$  E., 36 lks. dist.,  
marked T 5 N R 39 E S 19 B T.

A fir, 20 ins. diam., brs. S.  $37^{\circ}$  W., 70 lks. dist.,  
marked T 5 N R 38 E S 24 B T.

A fir, 20 ins. diam., brs. N.  $85^{\circ}$  W., 46 lks. dist.,  
marked T 5 N R 38 E S 13 B T.

From this Cor., the old Sec. Cor., a basalt stone, 10 x 10  
x 6 ins., above ground, marked & witnessed, as described  
by the surveyor general, brs. N. 2 chs. 50 lks. dist.,  
I destroy all traces of this old Sec. Cor.

Land; mountainous.

Soil; gravelly & stony, 3rd & 4th rates.

Timber; fir, pine, tamarack, spruce and hemlock.

Undergrowth; fir, pine, chaparral, hemlock, spruce, willow  
and bunch grass.

Mountainous land, 80 chs.