

## Subdivisional Lines, T 5 N R 38 E W M.

Chains	N.W. and S.E.
15.00	Leave timber; brs. N.80°E. and S.80°W.; trail, same.
20.00	Enter heavy timber; brs. N.40°W. and S.40°E.
21.15	A fir, 24 ins. diam., on line, I mark with 2 notches on N. AND S. sides.
25.00	Top of mountain; brs. N.50°W. and S.50°E.
27.00	Descend; brs. N.10°W. and S.10°E.
29.00	Steeper descent; brs. N.40°W. and S.40°E.
35.00	Descent brs. E. & W.
40.00	Set basalt stone, 30 x 20 x 18 ins., 22½ ins. in ground, with mound of stone, for ¼ Sec. Cor., marked ¼ on W. face from which A fir, 30 ins. diam., brs. N.30°E., 14 lks. dist., marked ¼ S 24 B T. A fir, 24 ins. diam., brs. S.42°W., 18 lks. dist., marked ¼ S 23 B T.
45.00	Down ridge point.
56.25	Foot of hill; branch, 10 lks. wide, runs E.; ascend. steep hillside; brs. N.60°W. and S.60°E.
60.00	Enter scattering timber.
64.00	Hill brs. N.30°W. and S.30°E.
70.00	Enter heavy timber, brs. N. & S.
80.00	A point, 500 ft. above Sec. Cor. S. and Set basalt stone, 30 x 15 x 15 ins., 22½ ins. in ground, with mound of stone, for Cor. of Secs. 13, 14, 23 & 24, marked with 3 notches on S. and 1 notch on E. edges; from which A fir, 15 ins. diam., brs. N.24½°E., 30 lks. dist., marked T 5 N R 38 E S 13 B T. A fir, 12 ins. diam., brs. S.54°E., 39 lks. dist., marked T 5 N R 38 E S 24 B T. A fir, 10 ins. diam., brs. S.40°W., 3 lks. dist., marked T 5 N R 38 E S 23 B T. A fir, 20 ins. diam., brs. N.84°W., 3 lks. dist., marked T 5 N R 38 E S 14 B T.
	Land; mountainous.