

Subdivisional Lines, T 5 N R 38 E W M.

Chains

1000 ft. above Closing Cor. on E.

Therefore, as recorded in the field notes of resurvey returned to the Surveyor-General, I

Set basalt stone, 24 x 10 x 10 ins., 18 ins. in ground, for $\frac{1}{4}$ Sec. Cor., N. Bdy. Sec. 4, at the temp. $\frac{1}{4}$ Sec. Cor. point, on line of old blazes, marked $\frac{1}{4}$ on N. face; from which

A fir, 24 ins. diam., brs. S. 7° E., 23 lks. dist., marked $\frac{1}{4}$ S 4 B T.

August 9, 1899.

August 3:

N. 0° 4' W., bet. Secs. 32 & 33.

Over stony bottom.

.50 Dry bed of stream, 6 lks. wide, course SW., water just below.

Ascend steep hill through undergrowth, brs. N. & S.

16.00 Trail along summit of divide bet. N. & S. Forks of Walla Walla River, brs. N. 80° E. and S. 80° W.

Descend steep mountain through timber, and dense undergrowth, brs. N. 50° E. & S. 50° W.

40.00 A point, 500 ft. below Sec. Cor. and

Set basalt stone, 36 x 20 x 4 ins., 15 ins. in ground, (strike rock and place mound of stones firmly about Cor.) for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face; from which

A fir, 12 ins. diam., brs. N. 81 $\frac{1}{2}$ ° E., 67 lks. dist., marked $\frac{1}{4}$ S 33 B T.

A fir, 12 ins. diam., brs. W., 94 lks. dist., marked $\frac{1}{4}$ S 32 B T.

42.00 Ravine, brs. E. & W.

Ascend along W. slope.

45.00 Leave timber, brs. E. & W.

58.00 Top of rise.

Descend.

60.00 Enter heavy timber, brs. E. & W.