

## Subdivisional Lines, T 5 N R 38 E W M.

Chains	
	August 7:
	S.89°55'W.; on random line bet. Secs. 19 & 30.
40.00	Set temp. $\frac{1}{4}$ Sec. Cor.
80.43	Intersect W. Bdy. of Tp., 3 lks. S. of Cor. of Secs. 19 & 30, an ironstone, 16 x 12 x 4 $\frac{1}{2}$ ins., above ground, marked and witnessed, as described in the field notes of re-survey returned to the Surveyor-General.
	Thence I run
	N.89°56'E. on true line bet. Secs. 19 & 30.
	Descending through scattering timber.
	Hill slopes N.
7.33	Foot.
	N. Fork of Walla Walla River, 50 lks. wide, flows N.70°W.
	Ascend bank and cross bottom.
10.00	Trail along river, brs. N.W. & S.E.
	Ascend.
12.00	Top of spur, brs. S.
	Descend.
23.50	Branch, 10 lks. wide, runs S.
	Ascend.
	Hill brs. N.60°W. and S.60°E.
33.00	Top of point, brs. S.
	Descend.
39.00	Foot; dry bed of stream, 5 lks. wide, course S.40°W.
	Ascend steep hill, brs. N. & S.
40.43	A point, 200 ft. above Sec. Cor. and
	Set basalt stone, 15 x 8 x 6 ins., 10 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on N. face; from which
	A fir, 12 ins. diam., brs. S.66°W., 2 chs., 25 lks. dist., marked $\frac{1}{4}$ S 30 B T.
	A fir, 18 ins. diam., brs. N.62 $\frac{1}{2}$ °W., 1 ch., 14 lks. dist., marked $\frac{1}{4}$ S 19 B T.
41.00	Leave scattering timber.
48.25	Top of spur, brs. S.E.
	Descend steep hill, brs. N.50°E. & S.50°W.