

S. Bdy. of T. 5 S., R. 30 E., W. M.
 As surveyed by, George S. Pershin, U.S. Deputy Surveyor,
 Under Contract No. 362,
 Dated Aug. 2, 1880

Chains

E. on a true line along the S. Bdy. of Sec. 31.

Var. 19° 00' E.

40.00 Set Sand stone 20 x 12 x 10 on slight S. slope for $\frac{1}{4}$
 Sec. Cor.

A fir 20 ins. diam. brs. N. 42° W. 42 lks. dist.

A Pine 20 ins. diam. brs. S. 50° W. 29 lks. dist.

80.00 Set Basalt stone 16 x 8 x 7 on S.W. slope for Cor. to
 Secs. 31 and 32.

A Pine 20 ins. diam. brs. N. 73° W. 34 lks. dist.

A Pine 22 ins. diam. brs. N. 38° E. 22 lks. dist.

Land; surface rolling,

Soil; 2nd and 3rd and 1st rate. Heavy timber on W. $\frac{1}{2}$

mile on E. $\frac{1}{2}$ mile scattering Pine, Tamarack and Fir.

Occasional dense young timber underbrush.

E. on a true line along the S. Bdy of Sec. 32.

Var. 21° 15' E.

Rolling,

40.00 Set basalt stone 18 x 12 x 8 on S.W. slope for $\frac{1}{4}$ Sec. Cor.

A Pine 18 ins. diam. brs. N. 52° W. 80 lks. dist.

A Pine 12 ins. diam. brs. S. 50° E. 54 lks. dist.

80.00 Set basalt stone 20 x 10 x 8 on E. slope for Cor. to
 Sec. 32 and 33.

A Fir 15 ins. diam. brs. N. 52° W. 70 lks. dist.

A Pine 12 ins. diam. brs. N. 17° E. 62 lks. dist.

Land; surface rolling,

Soil; 2nd and 3rd rate. heavy timber with occasional

open glades. Pine, tamarack and Fir. Some young timber

underbrush, Tamarack and Fir.

E. on a true line along the S. Bdy. of Sec. 33.

Var. 19° 30' E.

40.00 Set Pine post on level for $\frac{1}{4}$ Sec. Cor.

A Fir 12 ins. diam. brs. N. 5° E. 24 lks. dist.

A Tamarack 8 ins. diam. brs. S. 5° E. 33 lks. dist.