

Exterior Lines of T. 5, S., R. 29 E., W.M.

Chains		Feet
.79	The $\frac{1}{4}$ Sec. Cor., and at	
.51	The Cor. to Secs. 19, 24, 25 & 30. Thence N. on the E. Bdy. of Sec. 24.	
.89	The $\frac{1}{4}$ Sec. Cor.	
81.64	The Cor. to Secs. 13, 18, 19 & 24. Thence N. on the E. Bdy. of Sec. 13.	
40.61	The $\frac{1}{4}$ Sec. Cor.	
81.34	The Cor. to Sec. 7, 12, 13 & 18. Thence N. on the E. Bdy. of Sec. 12.	
40.70	The $\frac{1}{4}$ Sec. Cor.	
81.57	The Cor. to Secs. 1, 6, 7 & 12. Thence N. on the E. Bdy. of Sec. 1	
40.40	The $\frac{1}{4}$ Sec. Cor.	
32.55	The Cor. to Tps. 4 & 5 S., Rs. 29 & 30 E. The alignment is good.	
	I therefor destroy all the old Cors. and remove all marks from the bearing trees and resurvey the E. Bdy as follows:	
	I begin at the Standard Cor. to T. 5 S., Rs. 29 and 30 E. on which is a post marked, T. 5 S., R. 30 E., S. 31 on the N.E., T. 5 S., R. 29 E., S. 36 on the N.W. faces, from which	
	A Pine, 20 ins. diam. brs. N. 113° W., 54 lks. dist. marked T. 5 S., R. 30 E., S. 31 S.C.B.T.	
	A Pine, 4 ins. diam. brs. N. 47° W., 72 lks. dist. marked T. 5 S., R. 29 E., S. 36, S.C.B.T.	
	Thence I run,	
	N. bet. Secs. 31 & 36,	
	Var. 19° E.	
40.00	Set a basalt stone 12 x 10 x 8 ins., 8 ins. in the ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on the W. face, from which, A Pine, 20 ins. diam. brs. N. 9° W., 54 lks. dist. marked $\frac{1}{4}$ S.B.T. A Pine, 20 ins. diam. brs. N. 70° E., 54 lks. dist. marked $\frac{1}{4}$ S.B.T.	
63.00	Brook, 4 lks. wide, runs S. 60° E.	
80.00	Set a basalt stone 15 x 13 x 5 ins., 10 ins. in ground for Cor. to Secs. 25, 30, 31 and 36, marked with 5 notches on the N. and 1 notch on the S. edges, from which,	