Subdivisional Lines of T. 5 S., R. 30 E., W.M.

Chains		Feet
39.90	Set basalt stone 13 x 10 x 6 ins., 9 ins. in ground for ¼ Sec. Cor., marked ¼ on N. face; from which,	
	A Pine 10 ins. diam. brs. S. 20° E., 134 lks. dist. marked ¼ S.B.T.	
	A Pine 30 ins. diam. brs. N. 85° W., 125 lks. dist. marked ¼ S.B.T.	
79.80	The Cor. to Secs. 16, 17, 20 and 21.	
	Land; rolling	
	Soil; 2nd rate.	
	Densely covered with forests of pine and fir timber, 79.80 Chs.	
	N. bet. Secs. 16 and 17.	
	Var, 21° E.	
	Along rolling hillside.	
26.50	Creek, 10 lks wide, course S. 20° W.	
31.00	Top of hill from creek, brs. N.E. and S.W.	
40.00	Set basalt stone 14 x 10 x 4 ins., 9 ins. in ground for ¼ Sec. Cor., marked ¼ on W. face; from which,	
	A Pine, 10 ins. diam. brs. S. 81° W. 42 lks. dist. marked ¼ S.B.T.	
	A Pine 30 ins. diam. brs. N. 16° E., 21 lks. dist. marked ¼ S.B.T.	
80.00	Set basalt stone 15 x 11 x 7 ins., 10 ins. in ground for Cor. to Secs. 8, 9, 16 and 17, marked with 4 notches on S. and E. edges; from which,	
	A Tamarack, 18 ins. diam. brs. N. 37° E., 53 lks. dist. marked T. 5 S., R. 30 E., S. 9 B.T.	
	A Pine, 8 ins. diam. brs. S. 27° E., 28 lks. dist. marked T. 5 S., R. 30 E., S. 16 B.T.	
	A Pine, 6 ins. diam. brs. S. 50° W., 21 lks. dist. marked T. 5 S., R. 30 E., S. 17 B.T.	
	A Pine 5 ins. diam. brs. N. 62° W. 23 lks. dist. marked T. 5 S., R. 30 E., S. 8 B.T.	
	Land; rolling,	
	Soil; 2nd rate.	