

South Bdy., T.5 S., R.31 E., W. M., Oregon.
 As surveyed by Geo. S. Pershin,
 Under Contract No. 362,
 Dated Aug. 2, 1880.

Chains	<p>E. on true line along the S. Bdy. of Sec. 31.</p> <p style="text-align: right;">Var. 21°00'E.</p> <p>Up steep face of bluff.</p> <p>40.00 Set basalt stone, 17 x 12 x 8, on S. face of bluff, for $\frac{1}{4}$ Sec. Cor.</p> <p style="padding-left: 40px;">A pine, 20 ins. diam., brs. N.73°E., 240 lks. dist., No tree near on S. side.</p> <p>45.00 On spur, extending S.E.</p> <p>54.00 In ravine, opening S.E.</p> <p>80.00 Set basalt stone, 16 x 10 x 6, on level flat, for Cor. to Secs. 31 & 32.</p> <p style="padding-left: 40px;">A pine, 22 ins. diam., brs. N.50°W., 78 lks. dist. A pine, 18 ins. diam., brs. N.66°E., 125 lks. dist.</p> <p>Land; surface very broken. Soil; 3rd rate, part worthless. Mostly scattering timber with occasional thick groves. Pine, tamarack & fir, no underbrush. Good grass.</p> <hr/> <p>E. on true line along S. Bdy. Sec. 32.</p> <p style="text-align: right;">Var. 20°30'E.</p> <p>40.00 Set basalt stone, 18 x 8 x 5, on steep S. face of bluff, for $\frac{1}{4}$ Sec. Cor.; raised mound of stone. No trees near.</p> <p>59.00 Steep, rocky bluff, N.E. & S.W., impossible to chain.</p> <p>Send flag to E. side of canyon & measure base, N. 600 lks. giving an angle of 12°12' by Nat. sines & Co. sines gives</p> <table style="margin-left: 40px; border: none;"> <tr> <td style="padding-right: 20px;">Sin</td> <td style="padding-right: 20px;">Co. Sin.</td> <td style="padding-right: 20px;">lks.</td> <td>lks.</td> </tr> <tr> <td>.2113 :</td> <td>9774: :</td> <td>600: :</td> <td>27.75</td> </tr> </table> <p>making</p> <p>86.75 to flag.</p> <p>I then measure back 5.50 and find that the</p> <p>80.00 True Cor. will be near the middle of Camas Creek, therefore at the nearest practicable point on line E. of creek, Set Cor., on offset, making it</p> <p>81.25 Set basalt stone, 18 x 10 x 8, on steep N.W face of creek bluff, for offset Cor. to Secs. 32 & 33.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam, brs. N.57°W., 34 lks. dist.</p>	Sin	Co. Sin.	lks.	lks.	.2113 :	9774: :	600: :	27.75
Sin	Co. Sin.	lks.	lks.						
.2113 :	9774: :	600: :	27.75						