

## Subdivisional Lines, T.5 S., R.31 E., W. M.

Chains	
40.00	Set basalt stone, 15 x 12 x 10, S. slope, for $\frac{1}{4}$ Sec. Cor. A pine, 40 ins. diam., brs. N.33°E., 35 lks. dist. A fir, 20 ins. diam., brs. S.28°W., 44 lks. dist. along W. face of bluff.
80.00	Set basalt stone, 16 x 12 x 8, on S.W. face of spur, in mound of stone, for Cor. to Secs. 28, 29, 32 & 33. A pine, 18 ins. diam., brs. S.21°E., 180 lks. dist. Land; surface very broken & precipitous & mountainous. Soil; 3rd rate & some worthless. Some scattering pine, tamarack & fir timber, some grass.
E. on random line bet. Secs. 28 & 33. Var.16°15'E.	
40.00	Set post for temp. $\frac{1}{4}$ Sec. Cor.
80.04	Intersected N. & S. line, 26 lks. S. of Cor. to Secs. 27, 28, 33 & 34, from which Cor., I run S.89°49'W. on true line bet. Secs. 28 & 33. Var.19°15'E.
40.02	Set basalt stone, 17 x 12 x 6, on slight E. slope, for $\frac{1}{4}$ Sec. Cor. A pine, 17 ins. diam., brs. N.34°W., 78 lks. dist. A pine, 16 ins. diam., brs. S.18°W., 16 lks. dist.
64.00	Begin descent of creek bluff.
80.00	The Cor. to Secs. 28, 29, 32 & 33. Land; surface undulating & broken. Soil; 3rd rate. Scattering pine, fir & tamarack timber, some grass.
N. bet. Secs. 28 & 29. Var.16°15'E.	
40.00	Set basalt stone, 18 x 12 x 10, on W. face of bluff, for $\frac{1}{4}$ Sec. Cor. A fir, 18 ins. diam., brs. N.45°E., 50 lks. dist. A pine, 18 ins. diam., brs. N. 26°W., 62 lks. dist.
48.00	Creek, 50 lks. wide, course S.W.
57.00	On spur extends E.
64.00	Creek, 50 lks. wide, course S.E.