

Exterior Lines of T. 5 S., R. 32 E., W.M.

Chains		Feet
	maker.) I run, N. on the E. Bdy. of Sec. 36. Var. 18° 45' E.	
4.00	Leave timber, course S.E. and N.W.	
40.00	Set Basalt stone, 14 x 12 x 3 on level in mound of stone for $\frac{1}{4}$ Sec. Cor.	
66.00	Begin descent of creek bluff, and enter timber, course N. W. and S.E.	
80.00	Set basalt stone, 14 x 10 x 7 on E. face of bluff for Cor. to Sec. 25, 36, 30 & 31.	
	A Tamarack, 8 ins. diam. brs. N. 30° E., 10 lks. dist.	
	A " 6 " " " S. 30° E., 19 " "	
	A " 16 " " " S. 32° W., 72 " "	
	A " 17 " " " N. 25° W., 43 " "	
	Land; surface S. 66 Chs. undulating, N. 14 Chs. steep hillside, Soil; 2nd and 3rd rate, S. 66 Chs. open and good grass. N. 14 Chs., heavy Pine, Fir & Tamarack timber with some underbrush.	
	N. on the E. Bdy. of Sec. 25 Var. 16° 05' E.	
	Along down E. face of creek bluff	
40.00	Set basalt stone, 14 x 12 x 10 in creek bottom for $\frac{1}{4}$ Sec. Cor.	
	A Spruce, 10 ins. diam. brs. N. 23° W., 14 lks. dist.	
	A " 6 " " " S. 22° E., 118 lks. dist.	
42.00	Gable creek, 30 lks. wide, course N.W.	
78.00	Leave timber, course S.E. and N.W.	
80.00	Set basalt stone, 18 x 14 x 4, in mound of stone on S.W. face of bluff for Cor. to Secs. 24, 25, 19 & 30.	
	A Pine, 28 ins. diam. brs. S. 4° E., 146 lks. dist.	
	A Pine, 26 ins. diam. brs. S. 12° W., 177 lks. dist.	
	No other trees. Land; surface very broken and precipitous. Soil; 3rd and small part 2nd rate. Heavy Tamarack, Pine &	