

Chains

N. bet. Secs. 1 & 6.

Var. 20° E.

- 40.00 Set post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ S. on W. face, from which
- A pine, 4 ins. diam., brs. S. 75° E., 66 lks. dist., marked $\frac{1}{4}$ S., B.T.
 - A pine, 12 ins. diam., brs. S. 84° W., 300 lks. dist., marked $\frac{1}{4}$ S., B.T.

Leave heavy timber.

- 80.00 Set basalt stone, 15 x 15 x 15 ins., 10 ins. in ground, for Cor. to Tps. 4 & 5 S., Rs. 33 $\frac{1}{2}$ & 34 E., marked with 6 notches on each edge and raised mound of stone, 3 ft. high and 5 ft. base alongside.

Land; rolling.

Soil; 2nd rate.

Heavily timbered with pine & fir, 40 chs.

Scattering timber, 40 chs.

Subdivisional Lines, T. 5 S., R. 33 $\frac{1}{2}$ E., W. M.
As surveyed by Rufus S. Moore, U.S. Deputy Surveyor,
Under same Contract & date.

Having run the exterior lines of the S. & E. Bdays. of this Tp., with the same compass & assistants, I deem it unnecessary to retrace the S. & E. bdays. of Sec. 36.

Survey commences Oct. 27, 1882, with a Burt's improved Solar Compass.

I commenced at the standard Cor. to Secs. 35 & 36, on S. Bdy. of Tp., which is a post, 4 $\frac{1}{2}$ ft. long, 4 ins. sq., 24 ins. in ground, marked S.C., T. 5 S., R. 33 $\frac{1}{2}$ E. on N. S. 36 on E. and S. 35 on W. faces, with 1 notch on E. & 5 notches on W. faces, from which

- A fir, 15 ins. diam., brs. N. 82° W., 27 lks. dist., marked T. 5 S., R. 33 $\frac{1}{2}$ E., S. 35, B.T.

- A fir, 16 ins. diam., brs. N. 33° E., 39 lks. dist., marked T. 5 S., R. 33 $\frac{1}{2}$ E., S. 36, B.T.

- A pine, 7 ins. diam., brs. S. 10° W., 20 lks. dist., marked