Subdivisional Lines of T. 6 S., R. 31 E., W.M.

Checked		Feet
	Foot of hill, brs. N.W. and S.E.	
	Ascend hill from creek, runs. N.W. and S.E.	
80.00	Set a basalt stone, 16 x 8 x 6, and mound of stone for	
	Cor. to Secs. 3, 4, 9 & 10.	
	Land; hilly	
	Soil; 2ndrate.	
	Heavy tamarack, fir, pine on S. 72.50 Chs. Scattering Pine	
	on remainder and	
	Dense young fir, Pine and Tamarack.	
	E. on a random line bet. Sec. 3 & 10	
40.00	Set a temp. ¼ Sec. Cor.	
80.07	Intersect N. and S. line, 146 lks. S. of Cor. to Secs.	
	2, 3, 10 & 11, from which Cor. I run	
	S. 88° 57' W. on a true line	
13.07	Top of ridge, brs. N. and S.	
19.27	Ravine, course N.	
26.07	Top of ridge, brs. N.W. and S.E.	
40.03	Set a basalt stone, 16 x 12 x 6, and mound of stone for	
	¼ Sec. Cor.	
80.07	To Cor. to Secs. 3, 4, 9 & 10.	
	Land; hilly, W. ¼ broken	
	Soil; 3rd rate.	
	Scattering pine and fir on W. ½; E. ½ open.	
	N. on true line bet. Secs. 3 & 4	
	Var. 22° E.	
8.40	Ravine, course W.	
22.60	Perpendicular cliff, 100 ft. high, brs. N.W. and S.E.	
26.00	Ravine, course W.	
40.00	Set a basalt stone, 16 x 14 x 7, in mound of stone for ¼	
	Sec. Cor.	
75.51	Intersect 1st Standard Parallel, 335 lks. E. of Standard	
	Cor. to Secs. 32 & 33.	
	Set a pine post for closing Cor., from which	