

For Grant Home June 26th 1910

J. I. S. C. 33. G. W. M.

Chains Links

Commencing at the corner of Sec. 17 - S - 17 & 18
thence West set pins

- 35 67 Vertices bluff elev. 17' 30' to flag dist 374
3 95
38 45 to flag
40 00 set temporary 1/4 Sec corner
80 90 to 1/16 corner personally set by myself on a former survey
thence 1/4 mi East on line
40 45 set Stone 18 x 9 x 5 in for 1/4 Sec corner from which
I made a bevelled 6 in diameter hole N 69° 15' E 75.16 dis-
thence 1/4 mi South through Center Sec 18
38 84 set flag on bluff and measure base 100 lks to the east and
find angle to be 8° 30' distance to flag 669 + 384 = 10.53
10 53 top of bluff
40 00 set temporary 1/16 cor for Center Sec. 18
80 00 a point 94 lks East of 1/4 Sec on lot Sec 18 & 19
160 50 a point 188 lks East of 1/4 Sec on lot Sec 19 & 30
North on same line
20 60 set Post for 1/16 c
40 12 " " " 1/16 cor Center Sec. 19
thence West 162° back bluff on west side of creek
thence N 20° 25' E along bluff 48.82 chains
" South 45.73 lks
From a point - 34.29 chains South of Center Sec. 19 thence N 26° E 249 lks
N 78° 10' E 1.60 N 16° S E 174 N 0° 20' E 3.27 N 0° 25' W 3.05 N 72° 55' E 3.13 N 0° 10' W 4.54 N 73° 50' E 1.81
N 0° 55' W 2.25 N 41° 8' 51.78 N 0° 5' E 7.53 West 8.67 ch to Cor. Sec 19. 13

John W. Kimbrell surveyor